

# **Oracle® Outside In Content Access**

Developer's Guide

Release 8.3.7

**E12846-02**

June 2011

Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

Primary Author: Mike Manier

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

---

---

# Contents

<b>Preface</b> .....	ix
Audience .....	ix
Documentation Accessibility .....	ix
Related Documents .....	ix
Conventions .....	ix
 <b>1 Introduction</b>	
1.1 What's New in Release 8.3.7 .....	1-1
1.2 What Does This Technology Do? .....	1-3
1.3 Architectural Overview .....	1-3
1.4 Definition of Terms .....	1-4
1.5 Directory Structure .....	1-5
1.6 How to Use Content Access .....	1-5
1.7 How to Use Text Access .....	1-6
1.8 Copyright Information .....	1-7
 <b>2 Windows Implementation Details</b>	
2.1 Installation .....	2-1
2.1.1 NSF Support .....	2-2
2.2 Libraries and Structure .....	2-2
2.3 The Basics .....	2-3
2.3.1 What You Need in Your Source Code .....	2-3
2.3.2 Options and Information Storage .....	2-4
2.3.3 Structure Alignment .....	2-4
2.4 Character Sets .....	2-4
2.4.1 Default API Character Set .....	2-4
2.4.2 Double-Byte Character Set Mapping .....	2-5
2.5 Runtime Considerations .....	2-5
2.6 Changing Resources .....	2-5
 <b>3 UNIX Implementation Details</b>	
3.1 Installation .....	3-1
3.1.1 NSF Support .....	3-1
3.2 Libraries and Structure .....	3-2
3.3 The Basics .....	3-3

3.3.1	What You Need in Your Source Code .....	3-3
3.3.2	Options and Information Storage.....	3-4
3.4	Character Sets .....	3-4
3.4.1	Default API Character Set.....	3-4
3.4.2	Double-Byte Character Set Mapping .....	3-4
3.5	Runtime Considerations .....	3-5
3.5.1	Signal Handling .....	3-5
3.5.2	Runtime Search Path and \$ORIGIN.....	3-5
3.6	Environment Variables .....	3-5
3.7	Changing Resources .....	3-6
3.8	HP-UX Compiling and Linking.....	3-6
3.9	IBM AIX Compiling and Linking .....	3-7
3.10	Linux Compiling and Linking .....	3-8
3.10.1	Library Compatibility .....	3-8
3.10.1.1	Motif Libraries.....	3-8
3.10.1.2	GLIBC and Compiler Versions.....	3-9
3.10.1.3	Other Libraries .....	3-9
3.10.2	Compiling and Linking.....	3-12
3.11	Oracle Solaris Compiling and Linking .....	3-12
3.11.1	Oracle Solaris SPARC.....	3-13
3.11.2	Oracle Solaris x86.....	3-13
3.12	FreeBSD Compiling and Linking.....	3-14

## 4 Data Access Common Functions

4.1	DAInit .....	4-1
4.2	DAThreadInit .....	4-1
4.3	DADeInit .....	4-2
4.4	DAOpenDocument.....	4-2
4.4.1	IOSPECSUBOBJECT Structure .....	4-4
4.4.2	IOSPECLINKEDOBJECT Structure .....	4-4
4.4.3	IOSPECARCHIVEOBJECT Structure .....	4-4
4.4.4	SCCDAOBJECT Structure .....	4-4
4.5	DACloseDocument.....	4-5
4.6	DARetrieveDocHandle .....	4-5
4.7	DASetOption .....	4-5
4.8	DAGetOption .....	4-6
4.9	DAGetFileId.....	4-7
4.10	DAGetFileIdEx .....	4-7
4.11	DAGetErrorString.....	4-8
4.12	DAGetObjectInfo.....	4-9
4.13	DAGetTreeCount .....	4-10
4.14	DAGetTreeRecord.....	4-10
4.14.1	SCCDATREENODE Structure .....	4-11
4.15	DAOpenTreeRecord .....	4-11
4.16	DAOpenRandomTreeRecord.....	4-12
4.16.1	DATREENODELOCATOR .....	4-12
4.16.2	SCCCA_TREENODELOCATOR: Tree Node Locator.....	4-12

4.17	DASaveInputObject.....	4-13
4.18	DASaveTreeRecord.....	4-13
4.19	DASaveRandomTreeRecord .....	4-14
4.19.1	DATREENODELOCATOR .....	4-15
4.19.2	SCCCA_TREELOCATOR: Tree Node Locator.....	4-15
4.20	DACloseTreeRecord .....	4-16
4.21	DASetStatCallback.....	4-16
4.22	DASetFileAccessCallback .....	4-17

## 5 Text Access Functions

5.1	TAOpenText .....	5-1
5.2	TACloseText .....	5-1
5.3	TARReadFirst.....	5-2
5.4	TARReadNext .....	5-3

## 6 Content Access Functions

6.1	CAOpenContent.....	6-1
6.2	CACloseContent.....	6-1
6.3	CARReadFirst.....	6-2
6.4	CARReadNext.....	6-2
6.4.1	SCCCAGETCONTENT Structure .....	6-3

## 7 Content Description

7.1	SCCCA_BEGINTAG/SCCCA_ENDTAG: Tagged Content .....	7-1
7.1.1	SCCCA_BEGINTAG Content Description.....	7-1
7.1.2	Tag Types.....	7-1
7.1.3	Document Property IDs .....	7-3
7.1.4	SCCCA_SUBDOCPROPERTY Document Properties .....	7-5
7.1.5	Mail Field IDs .....	7-6
7.2	SCCCA_COMMENTREFERENCE Content Description.....	7-8
7.3	SCCCA_BREAK: Content Breaks .....	7-9
7.4	SCCCA_CELL: Cell Boundary .....	7-9
7.4.1	SCCCA_CELL Content Description.....	7-9
7.5	SCCCA_FILEPROPERTY: File Property Content .....	7-9
7.5.1	SCCCA_FILEPROPERTY Content Description .....	7-9
7.6	SCCCA_GENERATED: Generated Information .....	7-10
7.6.1	SCCCA_GENERATED Content Description.....	7-10
7.7	SCCCA_OBJECT: SubObjects .....	7-10
7.7.1	SCCCA_OBJECT Content Description .....	7-10
7.8	SCCCA_RECORD: Archive Record .....	7-11
7.8.1	SCCCA_RECORD Content Description.....	7-11
7.9	SCCCA_SHEET: Sheet Names.....	7-11
7.9.1	SCCCA_SHEET Content Description.....	7-11
7.10	SCCCA_STYLECHANGE: Style Information.....	7-12
7.10.1	SCCCA_STYLECHANGE Content Description.....	7-12
7.11	SCCCA_TEXT: Text Content.....	7-12

7.11.1	SCCCA_TEXT Content Description.....	7-13
7.11.2	Special Text Character Substitutions .....	7-14
7.12	SCCCA_TREENODELOCATOR: Tree Node Locator.....	7-14
7.12.1	SCCCA_TREENODELOCATOR Content Description.....	7-14

## 8 Redirected IO

8.1	Using Redirected IO .....	8-1
8.2	IOClose .....	8-2
8.3	IORead .....	8-2
8.4	IOWrite .....	8-3
8.5	IOSeek .....	8-4
8.6	IOTell .....	8-4
8.7	IOGetInfo.....	8-5
8.7.1	IOGENSECONDARY and IOGENSECONDARYW Structures.....	8-6
8.7.2	File Types That Cause IOGETINFO_GENSECONDARY .....	8-7
8.8	IOSEEK64PROC / IOTELL64PROC .....	8-8
8.8.1	IOSeek64.....	8-8
8.8.2	IOTell64 .....	8-8

## 9 Implementation Issues

9.1	Running in 24x7 Environments .....	9-1
-----	------------------------------------	-----

## 10 Sample Applications

10.1	Building the Samples on a Windows System .....	10-1
10.2	Building the Samples on a UNIX System .....	10-1
10.3	An Overview of the Sample Applications.....	10-2
10.3.1	casample.....	10-2
10.3.2	tademo (Windows Only) .....	10-2
10.3.2.1	Overview .....	10-3
10.3.2.2	MainWndProc .....	10-3
10.3.2.3	DisplayWndProc.....	10-3
10.3.2.4	DoTextOpen .....	10-3
10.3.2.5	DoTextClose .....	10-4
10.3.2.6	DoSaveTextAs .....	10-4
10.3.2.7	DoTextBlockAccess .....	10-4
10.3.3	taredir (UNIX Only) .....	10-4
10.3.4	textdemo (UNIX Only).....	10-4

## A Copyrights and Licensing

A.1	Outside In Content Access Licensing.....	A-1
-----	--	-----

## B Content Access Options

B.1	Character Mapping.....	B-1
B.1.1	SCCOPT_DEFAULTINPUTCHARSET .....	B-1
B.1.2	SCCOPT_OUTPUTCHARACTERSET .....	B-2

B.1.3	SCCOPT_UNMAPPABLECHAR.....	B-3
B.2	Input Handling.....	B-4
B.2.1	SCCOPT_EXTRACTXMPMETADATA .....	B-4
B.2.2	SCCOPT_FALLBACKFORMAT.....	B-4
B.2.3	SCCOPT_FIFLAGS.....	B-5
B.2.4	SCCOPT_IGNORE_PASSWORD.....	B-5
B.2.5	SCCOPT_LOTUSNOTESDIRECTORY .....	B-6
B.2.6	SCCOPT_PARSEXMPMETADATA .....	B-6
B.2.7	SCCOPT_PDF_FILTER_REORDER_BIDI.....	B-7
B.2.8	SCCOPT_PROCESS_OLE_EMBEDDINGS.....	B-7
B.2.9	SCCOPT_TIMEZONE.....	B-8
B.3	Compression.....	B-9
B.3.1	SCCOPT_FILTERJPG .....	B-9
B.3.2	SCCOPT_FILTERLZW .....	B-9
B.4	Content Access Flags .....	B-10
B.4.1	SCCOPT_ENABLEALLSUBOBJECTS.....	B-10
B.4.2	SCCOPT_CA_FLAGS.....	B-11
B.4.3	SCCOPT_FORMATFLAGS .....	B-11
B.5	File System .....	B-12
B.5.1	SCCOPT_IO_BUFFERSIZE .....	B-12
B.5.1.1	SCCBUFFEROPTIONS Structure.....	B-12
B.5.2	SCCOPT_TEMPDIR .....	B-13
B.5.2.1	SCCUTTEMPDIRSPEC Structure .....	B-14
B.5.3	SCCOPT_DOCUMENTMEMORYMODE .....	B-14
B.5.4	SCCOPT_REDIRECTTEMPFILE.....	B-15

## Index





---

---

# Preface

This document describes the installation and usage of the Outside In Content Access Software Developer's Kit (SDK).

## Audience

This document is intended for developers who are integrating Outside In Content Access into Original Equipment Manufacturer (OEM) applications.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at  
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit  
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit  
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Related Documents

For more information, go to:

<http://www.oracle.com/technetwork/indexes/documentation/index.html#middleware>

and click on Outside In Technology.

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.

Convention	Meaning
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

---

# Introduction

Content Access is part of Oracle's family of OEM products known as Outside In Technology, a powerful document extraction, conversion and viewing technology that can access the information in more than 500 file formats. Content Access is a server-grade technology that provides developers with normalized access to content stored in documents across multiple platforms.

There may be references to other Outside In Technology SDKs within this manual. To obtain complete documentation for any other Outside In product, see:

<http://www.oracle.com/technetwork/indexes/documentation/index.html#middleware>

and click on Outside In Technology.

## 1.1 What's New in Release 8.3.7

- The updated list of supported formats is linked from the page <http://www.outsideinsdk.com/>. Look for the data sheet with the latest supported formats.

- New File IDs have been added. CA will output a value for all new FIs.

FI Defines, value and LO strings are:

FI\_FLASH9, 1727, "Macromedia Flash 9"

FI\_FLASH10, 1728, "Macromedia Flash 10"

FI\_WIN\_EXPLORERCMD, 2400, "Microsoft Windows Explorer Command File"

FI\_7Z, 1826, "7z Archive File"

FI\_TRILLIAN\_TEXT, 1341, "Trillian Text Log File"

FI\_TRILLIAN\_XML, 1342, "Trillian XML Log File"

FI\_LIVEMESSENGER, 1343, "Microsoft Live Messenger Log File"

FI\_AOLMESSENGER, 1344, "AOL Messenger Log File"

FI\_WINDOWSHHELP, 2402, "Windows Help File"

FI\_WIN\_COMPILEDHELP, 2403, "Windows Compiled Help File"

FI\_WIN\_SHORTCUT, 2401, "Windows shortcut"

FI\_TRUETYPEFONT, 2404, "TrueType Font File"

FI\_TRUETYPECOLLECTION, 2405, "TrueType Font Collection File"

FI\_TRUETYPEFONT\_MAC, 2406, "TrueType (MAC) Font File"

FI\_OUTLOOK\_MSG\_MAIL, 1143, "MS Outlook Mail File"

FI\_OUTLOOK\_OFT\_MAIL, 1311, "Outlook Mail Form Template"

FI\_OUTLOOK\_MSG\_APPT, 1345, "MS Outlook Appointment File"

FI\_OUTLOOK\_OFT\_APPT, 1346, "Outlook Appointment Form Template"

FI\_OUTLOOK\_MSG\_JOURNAL, 1347, "MS Outlook Journal File"

FI\_OUTLOOK\_OFT\_JOURNAL, 1348, "Outlook Journal Form Template"

FI\_OUTLOOK\_MSG\_CONTACT, 1349, "MS Outlook Contact File"

FI\_OUTLOOK\_OFT\_CONTACT, 1350, "Outlook Contact Form Template"

FI\_OUTLOOK\_MSG\_NOTE, 1351, "MS Outlook Note File"

FI\_OUTLOOK\_OFT\_NOTE, 1352, "Outlook Note Form Template"

FI\_OUTLOOK\_MSG\_TASK, 1353, "MS Outlook Task File"

FI\_OUTLOOK\_OFT\_TASK, 1354, "Outlook Task Form Template"

For backward compatability - we will define previous FIs to the MAIL ids.

```
#define FI_OUTLOOK_MSG      FI_OUTLOOK_MSG_MAIL
```

```
#define FI_OUTLOOK_OFT      FI_OUTLOOK_OFT_MAIL
```

- OIT's internal error processing has been updated and propagation of error codes throughout OIT has been improved. In many cases the error codes reported by OIT will now more accurately reflect the actual cause of the error. DAERR is now functionally the same as SCCERR and OIT API functions that return DAERR may return any of the SCCERR values defined in `sccerr.h`.
- Attachments in PDF Files are now supported.
- The NSF filter is now supported on Linux x86-32 and Solaris Sparc 32. See [NSF Support](#) in the Unix Implementation chapter for details about Unix environment variables.
- Bookmarks have been exposed in Content Access through a tagged set of content with type `SCCCA_BOOKMARK`; see [SCCCA\\_BEGINTAG/SCCCA\\_ENDTAG: Tagged Content](#). There is an optional bookmark name that will now be included in the bookmark if generated text is enabled. It will have a new Sub Type, `SCCCA_BOOKMARKTEXT`, on the generated text.
- Records in an archive or in an email archive include information about the object as well as the object itself. A new piece of content, `SCCCA_RECORD`, will now be output at the beginning of a record (see [SCCCA\\_RECORD: Archive Record](#)). The end of the record will be denoted with a flag, `SCCCA_ENDRECORD`, in `dwData4` of an `SCCCA_OBJECT`.
- `SCCCA_CELL` has been added to indicate the starting and ending position of a cell in a spreadsheet or database (see [SCCCA\\_CELL: Cell Boundary](#)).
- The [SCCOPT\\_TEMPDIR](#) option now supports `IOTYPE_UNICODEPATH` on Windows.
- The [SCCOPT\\_PDF\\_FILTER\\_REORDER\\_BIDI](#) option controls whether or not the PDF filter will attempt to reorder bidirectional text runs so that the output is in standard logical order as used by the Unicode 2.0 and later specification.
- The [SCCOPT\\_PROCESS\\_OLE\\_EMBEDDINGS](#) option controls which embeddings are to be processed as native (OLE) documents and which are processed using the alternate graphic.

## 1.2 What Does This Technology Do?

Outside In Content Access provides a simple interface to extract text and metadata from business documents. This technology is particularly useful for document indexing applications. The product is comprised of two modules: Content Access and Text Access. Benefits include:

- The ability to extract text from documents with automatic translation into a particular character set, such as Unicode or ANSI.
- Access to numerous additional properties of documents that store information such as author, keywords, typist, version notes, carbon copy, checked by, subject, character and paragraph attributes, and so forth.
- A common interface to the content of diverse file formats including word processing, spreadsheet, database, email, vector, and presentation formats.
- The Text Access module's specific functions have tight integration with Outside In Technology, such that text generated by the text access functions is highlighted in the Viewer.
- Text Access and Content Access generate the same raw text. However, the following points are important.
  - rawtext and Text Access will extract some text as unmappable characters because they cannot be annotated. This includes text that is not visible (for example, document properties, hidden text, and so on.).
  - rawtext and Text Access only operate on the top-most layer of the file, and will not extract text from embedded documents. Thus, not all visible text will be extractable via rawtext or Text Access.
  - Content Access can be used to extract hidden text, like document properties; and text from embedded documents.
  - It should be noted that other Outside In products offer powerful text extraction and tagging abilities, such as Search Export and XML Export.

## 1.3 Architectural Overview

The basic architecture of Content Access is the same across all supported platforms:

Filter/Module	Description
Input Filter	The input filters form the base of the architecture. Each one reads a specific file format or set of related formats and sends the data to the chunker module through a standard set of function calls. There are more than 150 of these filters that read more than 500 distinct file formats. Filters are loaded on demand by the data access module.
Chunker	The Chunker module is responsible for caching a certain amount of data from the filter and returning this data to the Content Access module.

Filter/Module	Description
Content Access	The Content Access module reads data from the chunker and repackages it in a way that is convenient for the developer. This repackaging process includes mapping characters to a particular character set and converting some data (such as paragraph and cell breaks) into representative characters. CA outputs non-visible text, provides a wealth of style information, provides the information needed for the consumer to process sub-documents, and optionally produces non-textual information such as numbers in spreadsheets.
Text Access	The Text Access module is similar to the Content Access module, although it is restricted to text. For more information, see <a href="#">Chapter 5, "Text Access Functions."</a>
Data Access	The Data Access module implements a generic API for access to files. It understands how to identify and load the correct filter for all the supported file formats. The module delivers to the developer a generic handle to the requested file, which can then be used to run more specialized processes. The Data Access module is responsible for providing a document for the Content Access module. Data Access conserves resources by creating only one file handle and one chunker handle for each file, even if it is opened in multiple Content Access instances. It also provides a unified platform for several modules in addition to Content Access, including Text Access and Remote Filter Access.

## 1.4 Definition of Terms

The following table provides definitions of some common terms.

Term	Definition
Developer	Someone integrating this technology into another technology or application. Most likely this is you, the reader.
Source File	The file the developer wishes to extract content from.
Data Access Module	The core of Outside In Data Access, in the SCCDA library.
Data Access Submodule (also referred to as "Submodule")	This refers to any of the Outside In Data Access modules, including SCCCA (Content Access) and SCCTA (Text Access), but excluding SCCDA (Data Access).
Document Handle (also referred to as "hDoc")	A Document Handle is created when a file is opened using Data Access (see <a href="#">Chapter 4, "Data Access Common Functions"</a> ). Each Document Handle may have any number of Subhandles.
Content Handle (also referred to as "hItem")	The handle created by a call to CAOpenContent or TAOpenText. Every Content Handle has a Document Handle associated with it. The DASetOption and DAGetOption functions in the Data Access Module may be called with any Content Handle or Document Handle. The DARetrieveDocHandle function returns the Document Handle associated with any Content Handle.

## 1.5 Directory Structure

Each Outside In product has an `sdk` directory, under which there is a subdirectory for each platform on which the product ships (for example, `ca/sdk/ca_win-x86-32_sdk`). Under each of these directories are the following three subdirectories:

- **docs**: Contains both a PDF and HTML version of the product manual.
- **redist**: Contains only the files that the customer is allowed to redistribute. These include all the compiled modules, filter support files, `.xsd` and `.dtd` files, `cmmmap000.bin`, and third-party libraries, like freetype.
- **sdk**: Contains the other subdirectories that used to be at the root-level of an `sdk` (`common`, `lib` (windows only), `resource`, `samplefiles`, and `samplecode` (previously `samples`). In addition, one new subdirectory has been added, `demo`, that holds all of the compiled sample apps and other files that are needed to demo the products. These are files that the customer should not redistribute (`.cfg` files, `exportmaps`, and so forth).

In the root platform directory (for example, `ca/sdk/ca_win-x86-32_sdk`), there are two files:

- **README**: Explains the contents of the `sdk`, and that `makedemo` must be run in order to use the sample applications.
- **makedemo** (either `.bat` or `.sh` – platform-based): This script will either copy (on Windows) or Symlink (on UNIX) the contents of `.../redist` into `.../sdk/demo`, so that sample applications can then be run out of the `demo` directory.

## 1.6 How to Use Content Access

Here's a step-by-step overview of how to obtain information from a source file using Content Access.

1. **Initialize Threading (Optional)**: Call `DAThreadInit` if running in multiple threads.
2. **Initialize DA**: Call `DAInit` to initialize the Data Access technology. This function needs to be called only once per application.
3. **Set "Null" options**: Certain options need to be set before the desired source file is opened. These options are identified by requiring a `NULL` handle type. They include, but aren't limited to:
  - `SCCOPT_FALLBACKFORMAT`
  - `SCCOPT_FIFLAGS`
  - `SCCOPT_TEMPDIR`
4. **Open the Source File**: `DAOpenDocument` is called to create a document handle that uniquely identifies the source file. This handle may be used in subsequent calls to the `CAOpenContent` function or the `open` function of any other Data Access Submodule, and will be used to close the file when access is complete. This allows the file to be accessed from multiple Data Access Submodules without reopening.
5. **Set other Options**: Once the source document has been opened, set any other desired options. Most options will be set at this time and are identified by requiring a `VTHDOC` handle type.
6. **Open a Handle to Content Access**: Using the document handle, `CAOpenContent` is called to obtain a content handle that identifies the file to the Content Access

module. This handle will be used in all subsequent calls to the Content Access functions.

7. Retrieve the first Information from the File: Call `CARReadFirst` to read the first piece of information from the file. Note: this step may be repeated to reread the file.
8. Retrieve other Information from the File: Repeatedly call `CARReadNext`, which will iteratively read through and process the file.
9. Process sub-documents (Optional): When you encounter a sub-document, you may process that sub-document by repeating steps 4-11. Sub-documents are identified by either the `SCCCA_OBJECT` type or the `SCCCA_LINKEDOBJECT` subtype of the `SCCCA_BEGIN` type. Note: the document handle and content handle will be different for the parent and sub-document.
10. Close the Content Access Handle: Call `CACloseContent` to terminate the content access for the file. After this function is called, the content handle will no longer be valid, but the document handle may still be used.
11. Close the Source File: `DACloseDocument` is called to close the source file. After calling this function, the document handle will no longer be valid.
12. De-initialize DA: `DADeInit` is called to de-initialize the Data Access technology.

## 1.7 How to Use Text Access

Here's a step-by-step overview of how to obtain information from a source file using Text Access.

1. Initialize Threading (Optional): Call `DAThreadInit` if running in multiple threads.
2. Initialize DA: Call `DAInit` to initialize the Data Access technology. This function needs to be called only once per application.
3. Set "Null" options: Certain options need to be set before the desired source file is opened. These options are identified by requiring a `NULL` handle type. They include, but aren't limited to:
  - `SCCOPT_FALLBACKFORMAT`
  - `SCCOPT_FIFLAGS`
  - `SCCOPT_TEMPDIR`
4. Open the Source File: `DAOpenDocument` is called to create a document handle that uniquely identifies the source file. This handle may be used in subsequent calls to the `TAOpenText` function or the open function of any other Data Access Submodule, and will be used to close the file when access is complete. This allows the file to be accessed from multiple Data Access Submodules without reopening.
5. Set other Options: Once the source document has been opened, set any other desired options. Most options will be set at this time and are identified by requiring a `VTHDOC` handle type.
6. Open a Handle to Text Access: Using the document handle, `TAOpenContent` is called to obtain a content handle that identifies the file to the Text Access module. This handle will be used in all subsequent calls to the Text Access functions.
7. Retrieve the first Information from the File: Call `TARReadFirst` to read the first piece of information from the file. Note: this step may be repeated to reread the file.



8. Retrieve other Information from the File: Repeatedly call TAReadNext, which will iteratively read through and process the file.
9. Close the Text Access Handle: Call TACloseText to terminate the text access for the file. After this function is called, the text handle will no longer be valid, but the document handle may still be used.
10. Close the Source File: DACloseDocument is called to close the source file. After calling this function, the document handle will no longer be valid.
11. De-initialize DA: DADeInit is called to de-initialize the Data Access technology.

## 1.8 Copyright Information

The following notice must be included in the documentation, help system, or About box of any software that uses any of Oracle's executable code:

**Outside In Content Access © 1991, 2011 Oracle.**

The following notice must be included in the documentation of any software that uses Oracle's TIF6 filter (this filter reads TIFF and JPEG formats):

**The software is based in part on the work of the Independent JPEG Group.**



---

## Windows Implementation Details

---

Content Access is delivered as a set of DLLs. For a list of the currently supported platforms, see:

<http://www.oracle.com/technetwork/indexes/documentation/index.html#middleware>

Click on Outside In Technology, then click the Certification Information PDF.

### 2.1 Installation

To install the demo version of the SDK, copy the contents of the ZIP archive (available on the web site) to a local directory of your choice.

This product requires the Visual C++ libraries included in the Visual C++ Redistributable Package available from Microsoft. There are three versions of this package (x86, x64, and IA64) for each corresponding version of Windows.

These can be downloaded from [www.microsoft.com/downloads](http://www.microsoft.com/downloads), by searching on the site for the packages `vcredist_x86.exe`, `vcredist_x64.exe`, or `vcredist_IA64.exe`. The required version of each of these downloads is the 2005 SP1 Redistributable Package.

The redistributable module that Outside In requires is `msvcr80.dll`.

The installation directory should contain the following directory structure:

Directory	Description
\docs	Includes release notes and HTML and PDF versions of the manual you are reading right now. The release notes contain information that is potentially more up-to-date than that found in this user guide and should therefore be read before you install the technology.
\redist	Contains a working copy of the Windows version of the technology.
\sdk\common	Contains the C include files needed to build or rebuild the technology.
\sdk\demo	Contains compiled executables of the sample applications.
\sdk\lib	Contains the library (.lib) files for <code>scca.dll</code> , <code>sccta.dll</code> , <code>scra.dll</code> , <code>sccda.dll</code> and <code>sccfi.dll</code> .
\sdk\resource	Contains localization resource files. For more information, see <a href="#">Section 2.6, "Changing Resources."</a>
\sdk\samplecode	Contains the source code for the sample application.
\sdk\samplefiles	Contains sample files designed to exercise the technology.

## 2.1.1 NSF Support

Notes Storage Format (NSF) files are produced by the Lotus Notes Client or the Lotus Domino server. The NSF filter is the only Outside In filter that requires the native application to be present to filter the input documents. Due to integration with an outside application, NSF support will not work with redirected I/O, when an NSF file is embedded in another file, or with IOTYPE\_UNICODEPATH. Either Lotus Notes version 8 or Lotus Domino version 8 must be installed on the same machine as OIT. On Windows, SCCOPT\_LOTUSNOTESDIRECTORY should be set to the directory containing the nnotes.dll. NSF support is only available on the Win32 platform, Linux x86-32, and Solaris Sparc 32.

## 2.2 Libraries and Structure

Here is an overview of the files contained in the main installation directory for this product:

### API DLLs

These DLLs implement the API. They should be linked with the developer's application. LIB files are included in the SDK.

File	Description
scca.dll	Content Access module (provides organized chunker data for the developer)
sccda.dll	Data Access module
sccfi.dll	File Identification module (identifies files based on their contents). The File ID Specification may not be used directly by any application or workflow without it being separately licensed expressly for that purpose.
sccta.dll	Text Access module (provides straight text data for the developer)

### Support DLLs

File	Description
sccch.dll	Chunker (provides caching of and access to filter data for the display engine)
sccfa.dll	Filter Access module
sccfmt.dll	Formatting module (resolves numbers to formatted strings)
sccfut.dll	Filter utility module
sccind.dll	Indexing engine
scclo.dll	Localization library (all strings, menus, dialogs and dialog procedures reside here)
sccole.dll	OLE rendering module
sccut.dll	Utility functions (including IO subsystem)
wvcore.dll	The GDI Abstraction layer

## Filter DLLs

File	Description
vs*.dll	Filters for specific file types (there are more than 150 of these filters, covering more than 500 file formats)
oitnsf.id	Support file for the vsnsf filter.
ltscsn10.dll	Support files for the vslwp filter
lwpapin.dll	
ltscsd13.tlb	
lwpapipn.dat	

## Premier Graphics Filters

File	Description
i*2.flt	30 .flt files (the import filters for premier graphics formats)
isgdi32.dll	Interface to premier graphics filters

## Additional Files

File	Description
adinit.dat	Support file for the vsacd2 filter
cmmap000.bin	Tables for character mapping (all character sets)
cmmap000.sbc	Tables for character mapping (single-byte character sets). Located in the common directory.
cmmap000.dbc	Identical to cmmap000.Bin, but renamed for clarity (.dbc = double-byte character). This file is located in the common directory.

## 2.3 The Basics

All the steps outlined in this section are used in the sample applications provided with the SDK. Looking at the code for the **simple** sample application is recommended for those wishing to see a real-world example of this process.

For detailed information about all sample applications included with this product, see [Chapter 10, "Sample Applications."](#)

### 2.3.1 What You Need in Your Source Code

Any source code that uses this product should `#include` the file `scca.h` (for Content Access) and/or `sccta.h` (for Text Access) and `#define` `WINDOWS` and `WIN32` or `WIN64`. For example, a Windows application might have a source file with the following lines:

```
#define WINDOWS          /* Will be automatically defined if your
                           compiler defines _WINDOWS */

#define WIN32
#include <scca.h>          /* If using ContentAccess */
#include <sccta.h>        /* If using Text Access */
```

The developer's application should be linked to the Content Access (and/or Text Access) and Data Access DLLs through the provided libraries (sccta.lib, sccca.lib and sccda.lib).

## 2.3.2 Options and Information Storage

One set of information is created by the technology, the default options. In the Windows implementation, this is built by the technology as needed, usually the first time the product is run. You do not need to ship this list with your application. The list is automatically regenerated if corrupted or deleted.

The files used to store this information are stored in a .oit subdirectory in the following location:

`\Documents and Settings\user name\Application Data`

If an .oit directory does not exist in the user's directory, the directory will be created automatically by the technology. The files are automatically regenerated if corrupted or deleted.

The file is:

\*.d = Display engine lists

---

---

**Note:** Some applications and services may run under a local system account for which there is no user's "application data" folder. The technology first does a check for an environment variable called OIT\_DATA\_PATH. Then it checks for APPDATA, and then LOCALAPPDATA. If none of those exist, the options files are put into the executable path of the UT module.

---

---

These file names are intended to be unique enough to avoid conflict for any combination of machine name and install directory. This allows the user to run products in separate directories without having to reload the files above. The file names are built from an 11-character string derived from the directory the Outside In technology resides in and the name of the machine it is being run on. The string is generated by code derived from the RSA Data Security, Inc. MD5 Message-Digest Algorithm.

## 2.3.3 Structure Alignment

Outside In is built with 8-byte structure alignment. This is the default setting for most Windows compilers. This and other compiler options that should be used are demonstrated in the files provided with the sample applications in `\sdk\samplefiles\win`.

## 2.4 Character Sets

This section provides information about character sets.

### 2.4.1 Default API Character Set

The strings passed in the Windows API are ANSI1252 by default.

## 2.4.2 Double-Byte Character Set Mapping

Please note that to optimize performance on systems that do not require DBCS support, a second character mapping bin file, that does not contain any of the DBCS pages, is now included. The second bin file will give additional performance benefits for English documents, but will not be able to handle DBCS documents. To use the new bin file, replace the `cmmmap000.bin` with the new bin file, `cmmmap000.sbc`. For clarity, a copy of the `cmmmap000.bin` file named `cmmmap000.dbc` has also been included. Both the `cmmmap000.sbc` and `cmmmap000.dbc` files are located in the `\sdk\common` directory of the technology.

## 2.5 Runtime Considerations

The files used by this product must be in the same directory as the developer's executable.

## 2.6 Changing Resources

Outside In Content Access ships with the necessary files for OEMs to change any of the strings in the technology as they see fit.

Strings are stored in the `lodlgstr.h` file found in the resource directory. The file can be edited using any text editor.

---

---

**Note:** Do not directly edit the `scclo.rc` file. Strings are saved with their identifiers in `lodlgstr.h`. If a new `scclo.rc` file is saved, it will contain numeric identifiers for strings, instead of their `#define`'d names.

---

---

Once the changes have been made, the updated `scclo.dll` file can be rebuilt using the following steps:

1. Compile the `.res` file:

```
rc /fo ".\scclo.res" /i "<path to header (.h) files folder>" /d "NDEBUG"
scclo.rc
```

2. Link the `scclo.res` file you've created with the `scclo.obj` file found in the resource directory to create a new `scclo.dll`:

```
link /DLL /OUT:scclo.dll scclo.obj scclo.res
```

---

---

**Note:** Developers should make sure they have set up their environment variables to build the library for their specific architecture. For Windows x86\_32, when compiling with VS 2005, the solution is to run `vsvars32.bat` (in a standard VS 2005 installation, this is found in `C:\Program Files\Microsoft Visual Studio 8\Common7\Tools\`). If this works correctly, you will see the statement, "Setting environment for using Microsoft Visual Studio 2005 x86 tools." If you do not complete this step, you may have conflicts that lead to unresolved symbols due to conflicts with the Microsoft CRT.

---

---

3. Embed the manifest (which is created in the \resource directory during step 2) into the new DLL:

```
mt -manifest scclo.dll.manifest -outputresource:scclo.dll;2
```

If you are not using Microsoft Visual Studio, substitute the appropriate development tools from your environment.

---

---

**Note:** In previous versions of Outside In, it was possible to directly edit the SCCLO.DLL using Microsoft Visual Studio. Outside In DLLs are now digitally signed. Editing the signed DLL is not advisable.

---

---



---

## UNIX Implementation Details

The UNIX implementation of Content Access is delivered as a set of shared libraries. For a list of the currently supported platforms, see:

<http://www.oracle.com/technetwork/indexes/documentation/index.html#middleware>

Click on Outside In Technology, then click the Certification Information PDF.

### 3.1 Installation

To install the demo version of the SDK, copy the tgz file corresponding to your platform (available on the web site) to a local directory of your choice. Decompress the tgz file and then extract from the resulting tar file as follows:

```
gunzip tgzfile
tar xvf tarfile
```

The installation directory should contain the following directory structure:

Directory	Description
/docs	Includes HTML and PDF versions of the manual you are reading right now.
/redist	Contains a working copy of the UNIX version of the technology.
/sdk/common	Contains the C include files needed to build or rebuild the technology.
/sdk/demo	Contains the compiled executables of the sample applications.
/sdk/resource	Contains localization resource files. For more information, see <a href="#">Section 3.7, "Changing Resources."</a>
/sdk/samplecode	Contains a subdirectory holding the source code for a sample application. For more information, see <a href="#">Chapter 10, "Sample Applications."</a>
/sdk/samplefiles	Contains sample files designed to exercise the technology.

#### 3.1.1 NSF Support

Notes Storage Format (NSF) files are produced by the Lotus Notes Client or the Lotus Domino server. The NSF filter is the only Outside In filter that requires the native application to be present to filter the input documents. Due to integration with an outside application, NSF support will not work with redirected I/O nor will it work when an NSF file is embedded in another file. Lotus Domino version 8 must be installed on the same machine as OIT. The NSF filter is currently only supported on

Win32, Linux x86-32, and Solaris Sparc 32. SCCOPT\_LOTUSNOTESDIRECTORY is a Windows-only option and is ignored on Unix.

Additional steps must be taken to prepare the system. It is necessary to know the name of the directory in which Lotus Domino has been installed. On Linux, this default directory is /opt/ibm/lotus/notes/latest/linux. On Solaris, it is /opt/ibm/lotus/notes/latest/sunspa.

- In the Lotus Domino directory, check for the existence of a file called "notes.ini". If the file "notes.ini" does not exist, create it in that directory and ensure that it contains the following single line:

[Notes]

- Add the Lotus Domino directory to the \$LD\_LIBRARY\_PATH environment variable.
- Set the environment variable \$Notes\_ExecDirectory to the Lotus Domino directory.

## 3.2 Libraries and Structure

On the UNIX platforms, Outside In technologies are delivered with a set of shared libraries. All libraries should be installed to a single directory. Depending upon your application, you may also need to add that directory to the system's runtime search path. For more information, see [Section 3.6, "Environment Variables."](#)

The following is a brief description of the included libraries and support files. Note that in instances where a file extension is listed as .\*, the file extension will vary for each UNIX platform (**sl** on HP/UX, **so** on Linux and Solaris, and **a** or **o** on IBM AIX):

### API Libraries

These libraries implement the API. They should be linked with the developer's application.

File	Description
libsc_ca.*	Content Access module (provides organized chunker data for the developer)
libsc_da.*	Data Access module
libsc_fi.*	File Identification module (identifies files based on their contents). <b>The File ID Specification may not be used directly by any application or workflow without it being separately licensed expressly for that purpose.</b>
libsc_ta.*	Text Access module (provides straight text data for the developer)

### Support Libraries

File	Description
libsc_ch.*	Chunker (provides caching of and access to filter data for the display engine)
libsc_fa.*	Filter Access module
libsc_fmt.*	Formatting module (resolves numbers to formatted strings)
libsc_fut.*	Filter utility module

File	Description
libsc_ind.*	Indexing engine
libsc_lo.*	Localization library (all strings, menus, dialogs and dialog procedures reside here)
libsc_ut.*	Utility functions, including IO subsystem
libsc_xp.*	XPrinter bridge
libwv_core.*	The Abstraction layer

### Filter Libraries

File	Description
libvs_.*	Filters for specific file types (there are more than 150 of these filters, covering more than 500 file formats)

### Premier Graphics Filters

File	Description
i*2.flt	These 30 .flt files are the import filters for premier graphics formats
isunx2.flt	Interface to premier graphics filters

### Additional Files

File	Description
adinit.dat	Support file for the vsacad and vsacd2 filters
cmmap000.bin	Tables for character mapping (all character sets)
cmmap000.sbc	Tables for character mapping (single-byte character sets). This file is located in the common directory.
cmmap000.dbc	Identical to cmmap000.Bin, but renamed for clarity (.dbc = double-byte character). This file is located in the <i>common</i> directory.
oitnsf.id	Support file for the vsnsf filter.

## 3.3 The Basics

All the steps outlined in this section are used in the sample applications provided with the SDK. Looking at the code for the **casample** sample application (see [Chapter 10, "Sample Applications"](#)) is recommended for a real world example of this process.

### 3.3.1 What You Need in Your Source Code

Any source code that uses this product should `#include` the file `sccca.h` (for Content Access) and/or `sccta.h` (for Text Access) and `#define UNIX`. For example, a 32-bit UNIX application might have a source file with the following lines:

```
#define UNIX
#include <sccca.h>      /* If using ContentAccess */
#include <sccta.h>      /* If using Text Access */
```

and a 64-bit UNIX application might have a source file with the following lines:

```
#define UNIX
#define UNIX_64
#include <sccta.h>
```

### 3.3.2 Options and Information Storage

Three sets of information are created by the technology: the default options, a list of available filters and a list of available display engines. In the UNIX implementations, these lists are built as needed, usually the first time the product is run. You do not need to ship these lists with your application.

These lists are stored in the \$HOME/.oit directory. If the \$HOME environment variable is not set, the files are placed in the same directory as the Outside In Technology. If a .oit directory does not exist in the user's \$HOME directory, the .oit directory will be created automatically by the technology. The files are automatically regenerated if corrupted or deleted.

The files are:

- \*.f: Filter lists
- \*.d: Display engine list
- \*.opt: Persistent options

The names of these option files end in \*.opt, and are intended to be unique enough to avoid conflict for any combination of machine name and install directory. This is intended to prevent problems with version conflicts when multiple versions of the Viewer Technology and/or other Viewer Technology-based products are installed on a single system. The file names are built from an 11-character string derived from the directory the Outside In technology resides in and the name of the machine it is being run on. The string is generated by code derived from the RSA Data Security, Inc. MD5 Message-Digest Algorithm.

## 3.4 Character Sets

This section provides information about character sets.

### 3.4.1 Default API Character Set

The strings passed in the UNIX API are ISO8859-1 by default.

### 3.4.2 Double-Byte Character Set Mapping

To optimize performance on systems that do not require DBCS support, a second character mapping bin file not containing any of the DBCS pages is now included. The second bin file gives additional performance benefits for English documents, but will not be able to handle DBCS documents. To use the new bin file, replace the cmmmap000.bin with the new bin file, cmmmap000.sbc. For clarity, a copy of the cmmmap000.bin file named cmmmap000.dbc has also been included. Both the cmmmap000.sbc and cmmmap000.dbc files are located in the /common directory of the technology.

## 3.5 Runtime Considerations

This section provides information about runtime considerations.

### 3.5.1 Signal Handling

This product traps and handles the following signals:

- SIGABRT
- SIGBUS
- SIGFPE
- SIGILL
- SIGINT
- SIGSEGV
- SIGTERM

To override the default handling of these signals you can set your own signal handlers. This can be done after the developer's application has called `DAInit()`.

---

**Note:** The Java Native Interface (JNI) allows Java code to call and be called by native code (C/C++ in the case of OIT). You may run into problems if Java isn't allowed to handle signals and forward them to OIT. If OIT catches the signals and forwards them to Java, the JVMs will sometimes crash. OIT installs signal handlers when `DAInit()` is called, so if you call OIT after the JVM is created, you will need to use `libsig`. Refer here for more information:

<http://www.oracle.com/technetwork/java/javase/index-137495.html>

---

### 3.5.2 Runtime Search Path and \$ORIGIN

Libraries and sample applications are all built with the `$ORIGIN` variable as part of the binaries' runtime search path. This means that at runtime, OIT libraries will automatically look in the directory they were loaded from to find their dependent libraries. You don't necessarily need to include the technology directory in your `LD_LIBRARY_PATH` or `SHLIB_PATH`.

As an example, an application that resides in the same directory as the OIT libraries and includes `$ORIGIN` in its runtime search path will have its dependent OIT libraries found automatically. You will still need to include the technology directory in your linker's search path at link time using something like `-L` and possibly `-rpath-link`.

Another example is an application that loads OIT libraries from a known directory. The loading of the first OIT library will locate the dependent libraries.

---

**Note:** This feature does not work on AIX and FreeBSD.

---

## 3.6 Environment Variables

There are a number of environment variables the UNIX implementation of the technology may use at run time. While described elsewhere, following is a short summary of those variables and their usage.

Variable	Description
\$PATH	Must be set to include the directory containing the .flt files. Only applicable to AIX.
\$LD_LIBRARY_PATH (FreeBSD, HP-UX Itanium 64, Linux, Solaris)	These variables help your system's dynamic loader locate objects at runtime. If you have problems with libraries failing to load, try adding the path to the Outside In libraries to the appropriate environment variable. See your system's manual for the dynamic loader and its configuration for details.
\$SHLIB_PATH (HP-UX PA-RISC 32)	
\$LIBPATH (AIX, iSeries)	
	Note that for products that have a 64-bit PA-RISC, 64-bit Solaris and Linux PPC/PPC64 distributable, they will also go under \$LD_LIBRARY_PATH.
\$HOME	Must be set to allow the system to write the option, filter and display engine lists. For more information, see <a href="#">Section 3.3.2, "Options and Information Storage."</a>

## 3.7 Changing Resources

All of the strings used in the UNIX versions of Outside In products are contained in a file called lodlgstr.h. This file, located in the resource directory, can be modified for internationalization and other purposes. Everything necessary to rebuild the resource library to use the modified source file is included with the SDK.

Along with lodlgstr.h, an object file, scclo.o has been provided that is necessary for the linking phase of the build. A makefile has also been provided for building the library. The makefile allows building on all of the UNIX platforms supported by Outside In. It may be necessary to make minor modifications to the makefile so that the system header files and libraries can be found for compiling and linking. There are standard INCLUDE and LIB make variables defined for each platform in the makefile. Edit these variables to point to the header files and libraries on your particular system. Other make variables are:

- TECHINCLUDE: May need to be edited to point to the location of the Outside In common header files that are supplied with the SDK.
- BUILDDIR: May need to be edited to point to the location of the makefile, lodlgstr.h, and scclo.o (which should all be in the same directory).

After these make variables are set, change to the build directory and type make. The resource library, libsc\_lo, will be built and placed in the appropriate platform-specific directory. To use this library, copy it into the directory where the Outside In product resides, and the new, modified resource strings will then be used by the technology.

Menu constants are included in lomenu.h in the common directory.

All dialog boxes are created directly in the viewer code internally and are compiled and linked in the normal compilation process. There are no separate resource files corresponding to the .rc files in the Windows code.

Additional viewer resources are defined in xsccvw.h, which is included in the code for the sample executables and the viewer.

## 3.8 HP-UX Compiling and Linking

In the following example, libsc\_ca.sl and libsc\_da.sl are the only libraries that need to be linked with the casample. Not all applications that use the Content Access module will require the use of these libraries. They can be loaded when the application starts

by linking them directly at compile time or they can be loaded dynamically by your application using library load functions (for example, `shl_load`).

The following are example command lines used to compile the sample application `casample` from the `/sdk/samplecode/unix` directory. The command lines are separated into sections for HP/UX and HP/UX on Itanium (which requires GCC). Please note that this command line is only an example. The actual command line required on the developer's system may vary. The example assumes that the include and library file search paths for the technology libraries and any required X libraries are set correctly. If they are not set correctly, the search paths for the include and/or library files must be explicitly specified via the `-I include file path` and/or `-L library file path` options, respectively, so that the compiler and linker can locate all required files.

### HP-UX on RISC

```
cc -w -o ../casample/unix/casample ../casample/unix/casample.c +DAportable -Ae
-I/usr/include -I../common -L../demo -L/usr/lib -lm -lsc_ca -lsc_da -DUNIX
-Wl,+s,+b,'$ORIGIN'
```

### HP-UX on Itanium (64 bit)

```
cc -w -o ../casample/unix/casample ../casample/unix/casample.c +DD64
-I../common -L../demo -L/usr/lib/hpux64 -lsc_da -lsc_ca -DUNIX -DUNIX_64
-Wl,+s,+b,'$ORIGIN'
```

## 3.9 IBM AIX Compiling and Linking

All libraries should be installed into a single directory and the directory must be included in the system's shared library path (`$LIBPATH`) as well as the executable path (`$PATH`).

---

**Note:** `$LIBPATH` must be set and must point to the directory containing the Outside In technology.

---

Outside In Technology has been updated to increase performance, at a cost of using more memory. It is possible that this increased memory usage may cause a problem on AIX systems, which can be very conservative in the amount of memory they grant to processes. If your application experiences problems due to memory limitations with Outside In, you may be able to fix this problem by using the "large page" memory model. If you anticipate viewing or converting very large files with Outside In technology, we recommend linking your applications with the `-bmaxdata` flag (for example, `'cc -o foo foo.c -bmaxdata:0x80000000'`). If you are currently seeing illegal instruction errors followed by immediate program exit, this is probably due to not using the large data model.

In the following example, the `libsc_ca.a` and `libsc_da.a` are the only libraries that must be linked with the `casample`. Not all applications that use the Content Access module will require the use of all of these libraries. They can be loaded when the application starts by linking them directly at compile time or they can be loaded dynamically by your application using library load functions (for example, `load(libsc_vw.o , ...)` and `loadbind`) with the `.o` versions of the libraries provided.

The following is an example command line used to compile the sample application `casample` from the `/sdk/samplecode/unix` directory. This command line is only an example. The actual command line required on the developer's system may vary. The example assumes that the include and library file search paths for the technology libraries and any required X libraries are set correctly. If they are not set correctly, the

search paths for the include and/or library files must be explicitly specified via the `-I include file path` and/or `-L library file path` options, respectively, so that the compiler and linker can locate all required files.

---

**Note:** Developers may need to use the `-qcpluscmt` flag to allow C++ style comments.

---

```
gcc -w -o ../casample/unix/casample ../casample/unix/casample.c -I../common
-L../demo -lsc_ca -lsc_da -DUNIX -DFUNCPROTO
```

Two versions of some AIX modules have been included in this package. Including the `libsc_vw.o` files on the compiler's command line with a path will cause that path to be hard coded in the executable. The `-L` option does not detect object files and forcing developers to keep a copy of this file in their own source directory would be clumsy at best. On the other hand, **load** does not work with library archive files, only with object files.

## 3.10 Linux Compiling and Linking

This section provides information about Linux compiling and linking.

### 3.10.1 Library Compatibility

This section provides information about library compatibility.

#### 3.10.1.1 Motif Libraries

On some Linux installations, particularly newer ones, the Motif libraries that are installed are not compatible with the libraries that are used to build the Outside In technology. This is known to be the case with most of the SuSE installations, for example. It is likely that you have a binary incompatibility if you try to build one of the Xwindows-based sample applications included with this product and see an error at compile time that looks like the following:

```
warning: libXm.so.3, needed by ../libsc_vw.so, may conflict with libXm.so.2
```

The proper solution to this problem is to install a compatible Motif library and use it to build your application. Often, the installation discs for your particular Linux platform will have the proper libraries. If your installation discs do not have the libraries, instructions for downloading a binary rpm can be found at <http://rpmfind.net/linux/RPM>.

If you are doing development, you will also need the proper header files, as well.

The following is a list of the Motif library versions used by Oracle when building and testing the Outside In binaries:

- x86 Linux: OpenMotif v. 2.2.3
- zSeries Linux: OpenMotif v. 2.2.3
- Itanium Linux: OpenMotif v. 2.1.30.



---

**Note:** If a directory needs to be specified for the compiler to find the shared libraries, it is recommended that the `$LD_LIBRARY_PATH` environment variable be used. This will prevent the compiler from hard-coding the library's current directory into the executable as the only directory to search for the library at run time. Instead, the system will first search the directories specified by `$LD_LIBRARY_PATH` for the library.

---

### 3.10.1.2 GLIBC and Compiler Versions

For each Linux platform supported by Outside In, the following table indicates the compiler version used and the minimum required version of the GNU standard C library upon which Outside In depends.

Distribution	Compiler Version	GLIBC Version
x86 Linux	3.3.2	libc.so.6 (2.2.4 or newer)
Itanium Linux	3.3.2	libc.so.6 (2.2.4 or newer)
zSeries Linux	3.3.6	libc.so.6 (2.3.2 or newer)

### 3.10.1.3 Other Libraries

In addition to `libc.so.6`, Outside In is dependent upon the following libraries:

- `libXm.so.3` (in particular, `libXm.so.3.0.2` or newer, due to issues in OpenMotif 2.2.2)
- `libstdc++.so.5.0.5`
- `libgcc.so.1`
- `libXt.so.6`

`libgcc_s.so.1` was introduced with GCC 3.0, so any distribution based on a pre-GCC 3.0 compiler will not include `libgcc_s.so.1`.

The following table summarizes what is included with the RedHat and SuSE distributions supported by Outside In and what needs to be added/modified to make Outside In run on these systems. Developers may have trouble building with `libstdc++.so.5` versions before 5.0.5 due to unversioned symbols. Upgrade to 5.0.5 to correct the problem.

### Libraries on Linux Systems as Distributed (IA32)

Advanced Server 3.0	Support Information
<code>libc.so.6</code> version	<code>/lib/libc-2.3.2</code>
<code>libstdc++</code>	<code>/usr/lib/libstdc++.so.5.0.3</code>
<code>libgcc_s.so.1</code>	<code>/lib/libgcc_s.so-3.2.3-20030829.so.1</code>
<code>libXm.so.X</code>	<code>libXm.so.2</code> (OpenMotif 2.1.30-8) <code>libXm.so.3.0.1</code> (OpenMotif 2.2.2-16)

Advanced Server 3.0	Support Information
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has the proper libstdc++.so.5</li> <li>■ Default system install includes libgcc_s.so.1</li> <li>■ Install X libraries</li> </ul>
Advanced Server 4.0	Support Information
libc.so.6 version	/lib/libc-2.3.4
libstdc++	/usr/lib/libstdc++.so.6.0.3
libgcc_s.so.1	/usr/lib/libgcc_s.so-3.4.3-20041213.so.1
libXm.so.X	libXm.so.2 (OpenMotif 2.1.30-11) libXm.so.3.0.2 (OpenMotif 2.2.3-6)
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Install Motif 2.2.3 from distribution media</li> <li>■ Install libstdc++.so.5 (included with gcc 3.2 - 3.3.6)</li> <li>■ Default system install includes libgcc_s.so.1</li> <li>■ Install X libraries</li> </ul>
SuSE 8.1	Support Information
libc.so.6 version	/lib/libc.so.6 (GLIBC 2.2.5)
libstdc++	/usr/lib/libstdc++.so.5.0.0
libgcc_s.so.1	/lib/libgcc_s.so.1
libXm.so.X	libXm.so.3.0.1
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has proper libstdc++.so.5</li> <li>■ Default system install has libgcc_so.1</li> <li>■ Install X libraries</li> </ul>
SuSE 9.0	Support Information
libc.so.6 version	/lib/libc.so.6 (GLIBC 2.3.4)
libstdc++	/usr/lib/libstdc++.so.5.0.6 + old libraries
libgcc_s.so.1	/lib/libgcc_s.so.1
libXm.so.X	libXm.so.3.0.1
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has proper libstdc++.so.5</li> <li>■ Default system install has libgcc_so.1</li> <li>■ Install X libraries</li> </ul>

## Libraries on Linux Systems as Distributed (IA64)

<b>SuSE 8.1</b>	<b>Support Information</b>
libc.so.6 version	/lib/libc.so.6 (GLIBC 2.2.5)
libstdc++	/usr/lib/libstdc++.so.5.0.0
libgcc_s.so.1	/lib/libgcc_s.so.1
libXm.so.X	libXm.so.3.0.1
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has proper libstdc++.so.5</li> <li>■ Default system install has libgcc_s.so.1</li> <li>■ Install X libraries</li> </ul>

<b>SuSE 9.0</b>	<b>Support Information</b>
libc.so.6 version	/lib/libc.so.6 (GLIBC 2.3.4)
libstdc++	/usr/lib/libstdc++.so.5.0.6 + old libraries
libgcc_s.so.1	/lib/libgcc_s.so.1
libXm.so.X	libXm.so.3.0.1
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has proper libstdc++.so.5</li> <li>■ Default system install has libgcc_s.so.1</li> <li>■ Install X libraries</li> </ul>

<b>SuSE Linux Enterprise Server 8.0</b>	<b>Support Information</b>
libc.so.6 version	/lib/libc.so.6.1 (GLIBC 2.2.6)
libstdc++	/usr/lib/libstdc++-libc6.2-2.so.3 /usr/lib/libstdc++.so.5.0.0
libgcc_s.so.1	/lib/libgcc_s.so.1
libXm.so.X	libXm.so.3.0.1
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3.0.2 (OpenMotif &gt;=2.2.3)</li> <li>■ Default system install has proper libstdc++.so.5.</li> <li>■ Default system install has libgcc_s.so.1</li> <li>■ Install X libraries</li> </ul>

## Libraries on Linux PPC Systems

<b>SuSE Linux Enterprise Server 10 PPC</b>	<b>Support Information</b>
libc.so.6 version	/lib/libc.so.6 (GLIBC 2.3.4 or higher)
libstdc++	/usr/lib/libstdc++.so.6.0.8
libgcc_s.so.1	/lib/libgcc_s.so.1

SuSE Linux Enterprise Server 10 PPC	Support Information
libXm.so.X	libXm.so.3
Required to Use Outside In	<ul style="list-style-type: none"> <li>■ Update to &gt;= libXm.so.3 (OpenMotif &gt;=2.2.2 &lt; 2.2.3)</li> <li>■ Default system install has proper libstdc++.so.6.0.8</li> <li>■ Default system install has libgcc_so.1</li> <li>■ Install X libraries</li> </ul>

### 3.10.2 Compiling and Linking

In the following example, the libsc\_ca.so and libsc\_da.so are the only libraries needing to be linked with the casample. Not all applications that use the Content Access module will require the use of all of these libraries. They can be loaded when the application starts by linking them directly at compile time or they can be loaded dynamically by your application using library load functions (for example, dlopen).

The following is an example command line used to compile the sample application **casample** from the /sdk/samplecode/unix directory. Please note that this command line is only an example. The actual command line required on the developer's system may vary. The example assumes that the include and library file search paths for the technology libraries and any required X libraries are set correctly. If they are not set correctly, the search paths for the include and/or library files must be explicitly specified via the *-I include file path* and/or *-L library file path* options, respectively, so the compiler and linker can locate all required files.

#### Linux 32-bit (includes Linux PPC)

```
gcc -w -o ../casample/unix/casample ../casample/unix/casample.c
-I/usr/local/include -I../common -L../demo -L/usr/local/lib -lsc_da -lsc_ca
-DUNIX -Wl,-rpath,../demo -Wl,-rpath,'${ORIGIN}'
```

#### Linux 64-bit

```
gcc -w -o ../casample/unix/casample ../casample/unix/casample.c
-I/usr/local/include -I../common -L../demo -L/usr/local/lib -lsc_da -lsc_ca
-DUNIX -DUNIX_64 -Wl,-rpath,../demo -Wl,-rpath,'${ORIGIN}'
```

#### Linux zSeries

```
gcc -w -o ../casample/unix/casample ../casample/unix/casample.c
-I/usr/local/include -I../common -L../demo -L/usr/local/lib -lsc_da -lsc_ca
-DUNIX -Wl,-rpath,../demo -Wl,-rpath,'${ORIGIN}'
```

## 3.11 Oracle Solaris Compiling and Linking

All libraries should be installed into a single directory.

---

**Note:** This product does not support the old Solaris BSD mode.

---

In the following example, the libsc\_ca.so and libsc\_da.so are the only libraries that need to be linked with the casample. Not all applications that use the Content Access module will require the use of all of these libraries. They can be loaded when the application starts by linking them directly at compile time or they can be loaded dynamically by your application using library load functions (for example, dlopen).

The following is an example command line used to compile the sample application `casample` from the `/sdk/samplecode/unix` directory. Please note that this command line is only an example. The actual command line required on the developer's system may vary. The example assumes that the include and library file search paths for the technology libraries and any required X libraries are set correctly. If they are not set correctly, the search paths for the include and/or library files must be explicitly specified via the `-I include file path` and/or `-L library file path` options, respectively, so that the compiler and linker can locate all required files.

---

**Note:** Developers may need to use the `-xc` flag to allow C++ style comments.

---

### 3.11.1 Oracle Solaris SPARC

```
cc -I/usr/include -I/usr/dt/share/include -I../common -w -o
../casample/unix/casample ../casample/unix/casample.c -L../demo -L/usr/lib
-L/lib -lc -ldl -lsc_ca -lsc_da -DUNIX -Wl,-R,'$ORIGIN'
```

**Note:** When running the 32-bit SPARC binaries on Solaris 9 systems, you may see the following error:

```
ld.so.1: simple: fatal: libm.so.1: version `SUNW_1.1.1' not found
(required by file ./libsc_vw.so)
```

This is due to a missing system patch. Please apply the following patch (or its successor) to your system to correct.

- For Solaris 9 - Patch 111722-04

### 3.11.2 Oracle Solaris x86

---

**Note:** Your system will require Solaris patch 108436, which contains the C++ library `libCstd.so.1`.

---

```
cc -I/usr/include -I/usr/dt/share/include -I../common -w -o
../casample/unix/casample ../casample/unix/casample.c -L../demo -L/usr/lib
-lsc_ca -lsc_da -DUNIX -R '$ORIGIN'+ -DUNIX
```

## 3.12 FreeBSD Compiling and Linking

The following is an example command line used to compile the sample application `casample` from the `/sdk/samplecode/unix` directory. Please note that this command line is only an example. The actual command line required on the developer's system may vary. The example assumes that the include and library file search paths for the technology libraries and any required X libraries are set correctly. If they are not set correctly, the search paths for the include and/or library files must be explicitly specified via the `-I include file path` and/or `-L library file path` options, respectively, so the compiler and linker can locate all required files.

```
gcc -w -o ../casample/unix/casample ../casample/unix/casample.c
-I/usr/local/include -I../common -L../demo -L/usr/local/lib -lsc_da -lsc_ca
-DUNIX -Wl,-rpath,../demo
```

---

## Data Access Common Functions

---

The Data Access module is common to all Outside In technologies. It provides a way to open a generic handle to a source file. This handle can then be used in the functions described in this chapter.

### 4.1 DAINit

This function tells the Data Access module to perform any necessary initialization it needs to prepare for document access. This function must be called before the first time the application uses the module to retrieve data from any document.

---

**Note:** DAINit should only be called once per application, at application startup time. Any number of documents can be opened for text access between calls to DAINit and DADeInit. If DAINit succeeds, DADeInit must be called regardless of any other API calls.

---

#### Prototype

```
DAERR DAINit();
```

#### Return Values

- DAERR\_OK: If the initialization was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

### 4.2 DATHreadInit

DATHreadInit initializes the technology, preparing it to be run in a thread. This preparation includes setting up mutex function pointers to prevent threads from clashing in critical sections of the technology's code. The developer must actually code the threads after this function has been called. DATHreadInit should be called just before the call to DAINit and only once per process. Both functions should be called before the developer's application begins the thread.

---

**Note:** Multiple threads are supported for all Windows platforms and the 32-bit versions of Linux x86 and Solaris SPARC. The DATHreadInit function is required on all of these platforms. Failed initialization of this function will not impair other API calls. If the function is not called or fails, stub functions are called instead of mutex functions.

---

**Prototype**

```
VTLONG DATHreadInit(VTSHORT ThreadOption);
```

**Parameters**

- ThreadOption: One of the following values:
  - DATHREAD\_INIT\_NOTHEADS: No thread support requested.
  - DATHREAD\_INIT\_PTHREADS: Support for PTHREADS requested.
  - DATHREAD\_INIT\_NATIVETHREADS: Support for native threading requested. Supported only on Oracle Solaris.

**Return Values**

- DATHREAD\_INIT\_SUCCESS: The initialization was successful.
- DATHREAD\_INIT\_FAILED: The initialization was unsuccessful.
- DATHREAD\_INIT\_ALREADY\_CALLED: DATHreadInit has already been initialized. This value will be returned if DATHreadInit is called more than once in an application.
- DAERR\_OK: If the initialization was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.3 DADeInit

This function tells the Data Access module that it will not be asked to read additional documents, so it should perform any cleanup tasks that may be necessary. This function should be called at application shutdown time, and only if the module was successfully initialized with a call to DAINit.

**Prototype**

```
DAERR DADeInit();
```

**Return Values**

- DAERR\_OK: If the de-initialization was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.4 DAOpenDocument

Opens a source file to make it accessible by one or more of the data access technologies. If DAOpenDocument succeeds, DACloseDocument must be called regardless of any other API calls.

**Prototype**

```
DAERR DAOpenDocument(  
    VTLPDOC    phDoc,  
    VTDWORD    dwSpecType,  
    VTLPVOID    pSpec,  
    VTDWORD    dwFlags);
```



## Parameters

- **lphDoc**: Pointer to a handle that will be filled with a value that uniquely identifies the document to data access. The developer will use this handle in subsequent calls to data access to identify this particular source file.

This is *not* an operating system file handle.

- **dwSpecType**: Describes the contents of **pSpec**. Together, **dwSpecType** and **pSpec** describe the location of the source file. Must be one of the following values:
  - **IOTYPE\_ANSIPATH**: Windows only. **pSpec** points to a NULL-terminated full path name using the ANSI character set and FAT 8.3 (Win16) or NTFS (Win32 and Win64) file name conventions.
  - **IOTYPE\_UNICODEPATH**: Windows only. **pSpec** points to a NULL-terminated full path name using the Unicode character set and NTFS (Win32 and Win64) file name conventions.
  - **IOTYPE\_UNIXPATH**: X Windows on UNIX platforms only. **pSpec** points to a NULL-terminated full path name using the system default character set and UNIX path conventions.
  - **IOTYPE\_SUBOBJECT**: All platforms. Opens an embedded object for data access. **pSpec** points to a structure **IOSPECSUBOBJECT** (see [Section 4.4.1, "IOSPECSUBOBJECT Structure"](#)) that has been filled with values returned in a **SCCCA\_OBJECT** content entry from Content Access.
  - **IOTYPE\_REDIRECT**: All platforms. **pSpec** points to a developer-defined struct that allows the developer to redirect the IO routines used to read the file.
  - **IOTYPE\_ARCHIVEOBJECT**: All platforms. Opens an embedded archive object for data access. **pSpec** points to a structure **IOSPECARCHIVEOBJECT** (see [Section 4.4.3, "IOSPECARCHIVEOBJECT Structure"](#)) that has been filled with values returned in a **SCCCA\_OBJECT** content entry from Content Access.
  - **IOTYPE\_LINKEDOBJECT**: All platforms. Opens an object specified by a linked object for data access. **pSpec** points to a structure **IOSPECLINKEDOBJECT** (see [Section 4.4.2, "IOSPECLINKEDOBJECT Structure"](#)) that has been filled with values returned in an **SCCCA\_BEGIN TAG** or **SCCCA\_END TAG** with a subtype of **SCCCA\_LINKEDOBJECT** content entry from Content Access.
  - **IOTYPE\_OBJECT**: All platforms. Opens an object (archive, embedded, or linked) for data access. **pSpec** points to a structure **SCCDAOBJECT** (see [Section 4.4.4, "SCCDAOBJECT Structure"](#)) that has been filled with values from Content Access (**SCCCA\_OBJECT** or **SCCCA\_BEGIN TAG** with a subtype of **SCCCA\_LINKEDOBJECT**) or from the <document> element in the SearchML flavor of Search Export.
- **pSpec**: File location specification.
- **dwFlags**: The low WORD is the file ID for the document (0 by default). If you set the file ID incorrectly, the technology will fail. If set to 0, the file identification technology will determine the input file type automatically. The high WORD should be set to 0. It may also be set to the following flags:
  - **DAOPENDOCUMENT\_ARCHIVEONLYMODE**: This flag may only be used with archive files. It opens the archive in a special mode that is only usable with [DASaveRandomTreeRecord](#) and [DAOpenRandomTreeRecord](#).
  - **DAOPENDOCUMENT\_CONTINUEONFAILURE**: Some embeddings may have both an OLE representation and an alternate graphic. When this flag is

set for `IOTYPE_OBJECT`, the technology will first try to access the OLE representation. If there are errors, it will then attempt to access the alternate graphic.

### Return Values

- `DAERR_OK`: Returned if the open was successful. Otherwise, one of the other `DAERR_` values in `scda.h` or one of the `SCCERR_` values in `scerr.h` is returned.

## 4.4.1 IOSPECSUBOBJECT Structure

```
typedef struct IOSPECSUBOBJECTtag
{
    VTDWORD      dwStructSize;
    VTSYSPARAM    hDoc;           /* Parent Doc hDoc */
    VTDWORD      dwObjectId;      /* Object Identifier */
    VTDWORD      dwStreamId;      /* Stream Identifier */
    VTDWORD      dwReserved1;     /* Must always be 0 */
    VTDWORD      dwReserved2;     /* Must always be 0 */
} IOSPECSUBOBJECT, * PIOSPECSUBOBJECT;
```

## 4.4.2 IOSPECLINKEDOBJECT Structure

```
typedef struct IOSPECLINKEDOBJECTtag
{
    VTDWORD      dwStructSize;
    VTSYSPARAM    hDoc;
    VTDWORD      dwObjectId;      /* Object identifier. */
    VTDWORD      dwType;          /* Linked Object type */
                                /* (SO_LOCATOR_TYPE_*) */
    VTDWORD      dwParam1;        /* parameter for DoSpecial call */
    VTDWORD      dwParam2;        /* parameter for DoSpecial call */
    VTDWORD      dwReserved1;     /* Reserved. */
    VTDWORD      dwReserved2;     /* Reserved. */
} IOSPECLINKEDOBJECT, * PIOSPECLINKEDOBJECT;
```

## 4.4.3 IOSPECARCHIVEOBJECT Structure

```
typedef struct IOSPECARCHIVEOBJECTtag
{
    VTDWORD      dwStructSize;
    VTDWORD      hDoc;            /* Parent Doc hDoc */
    VTDWORD      dwNodeId;        /* Node ID */
    VTDWORD      dwStreamId;
    VTDWORD      dwReserved1;     /* Reserved */
    VTDWORD      dwReserved2;     /* Reserved */
} IOSPECARCHIVEOBJECT, * PIOSPECARCHIVEOBJECT;
```

## 4.4.4 SCCDAOBJECT Structure

```
typedef struct SCCDAOBJECTtag
{
    VTDWORD      dwSize;          /* sizeof(SCCDAOBJECT) */
    VTHDOC        hDoc;           /* DA handle for the document
                                   containing the object */
    VTDWORD      dwObjectType;    /* SCCCA_EMBEDDEDOBJECT,
                                   SCCCA_LINKEDOBJECT,
                                   SCCCA_COMPRESSEDFILE or
                                   SCCCA_ATTACHMENT */
}
```

```

VTDWORD   dwData1;           /* Data identifying the object */
VTDWORD   dwData2;           /* Data identifying the object */
VTDWORD   dwData3;           /* Data identifying the object */
VTDWORD   dwData4;           /* Data identifying the object */
} SCCDAOBJECT, * PSCCDAOBJECT;

```

## 4.5 DACloseDocument

This function is called to close a file opened by the reader that has not encountered a fatal error.

### Prototype

```

DAERR DACloseDocument(
    VTHDOC hDoc);

```

### Parameters

- hDoc: Identifier of open document. Must be a handle returned by the DAOpenDocument function.
- DAERR\_OK: Returned if close succeeded. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.6 DAREtrieveDocHandle

This function returns the document handle associated with any type of Data Access handle. This allows the developer to only keep the value of hItem, instead of both hItem and hDoc.

### Prototype

```

DAERR DAREtrieveDocHandle(
    VTHDOC     hItem,
    VTLPDOC     phDoc);

```

### Parameters

- hItem: Identifier of open document. May be the subhandle returned by the DAOpenDocument or DAOpenTreeRecord functions in the data access submodule. Passing in an hDoc created by DAOpenDocument for this parameter will result in an error.
- phDoc: Pointer to a handle that will be filled with the document handle associated with the passed subhandle.

### Return Value

- DAERR\_OK: Returned if the handle in phDoc is valid. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.7 DASetOption

This function is called to set the value of a data access option.

### Prototype

```

DAERR DASetOption(
    VTHDOC     hDoc,
    VTDWORD     dwOptionId,

```

```
VTLPVOID    pValue,  
VTDWORD     dwValueSize);
```

### Parameters

- **hDoc**: Identifier of open document. May be a VTHDOC returned by the DAOpenDocument function, or the subhandle returned by the DAOpenDocument or DAOpenTreeRecord functions (VTHCONTENT, VTHTEXT, and so forth). Setting an option for a VTHDOC will affect all subhandles opened under it, while setting an option for a subhandle will only affect that handle.

If this parameter is NULL, then setting the option will affect all documents opened thereafter. Once an option is set using the NULL handle, this option becomes the default option thereafter. Note that this parameter should only be set to NULL if the option being set can take that value.

- **dwOptionId**: The identifier of the option to be set.
- **pValue**: Pointer to a buffer containing the value of the option.
- **dwValueSize**: The size in bytes of the data pointed to by pValue. For a string value, the NULL terminator should be included when calculating dwValueSize.

### Return Value

- **DAERR\_OK**: Returned if DASETOption succeeded. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.8 DAGetOption

This function is called to retrieve the value of a data access option. Note that the results of a call to this option are only valid if DASETOption has already been called on the option.

### Prototype

```
DAERR DAGetOption(  
    VTHDOC    hItem,  
    VTDWORD   dwOptionId,  
    VTLPVOID  pValue,  
    VTLPDWORD pSize);
```

### Parameters

- **hItem**: Identifier of open document. May be a VTHDOC returned by the DAOpenDocument function, or the subhandle returned by the DAOpenDocument or DAOpenTreeRecord functions (VTHCONTENT, VTHTEXT, and so forth). Getting an option for a VTHDOC will get the value of that option for that handle, which may be different than the subhandle's value.
- **dwOptionId**: The identifier of the option to be returned. For a list of option IDs with descriptions, see [Chapter 7, "Content Description."](#)
- **pValue**: Pointer to a buffer containing the value of the option.
- **pSize**: This VTDWORD should be initialized by the caller to the size of the buffer pointed to by pValue. If this size is sufficient, the option value will be copied into pValue and pSize will be set to the actual size of the option value. If the size is not sufficient, pSize will be set to the size of the buffer needed for the option and an error will be returned.

**Return Value**

- **DAERR\_OK**: Returned if DAGetOption was successful. Otherwise, one of the other **DAERR\_** values in `sccda.h` or one of the **SCCERR\_** values in `sccerr.h` is returned.

## 4.9 DAGetFileId

This function allows the developer to retrieve the format of the file based on the technology's content-based file identification process. This can be used to make intelligent decisions about how to process the file and to give the user feedback about the format of the file they are working with.

Note: in cases where File ID returns a value of **FI\_UNKNOWN**, then this function will apply the Fallback Format before returning a result.

**Prototype**

```
DAERR DAGetFileId(
    VTHDOC      hDoc,
    VTLPDWORD   pdwFileId);
```

**Parameters**

- **hDoc**: Identifier of open document. May be a **VTHDOC** returned by the **DAOpenDocument** function, or the subhandle returned by the **DAOpenDocument** or **DAOpenTreeRecord** functions (**VTHEXPORT**, **VTHCONTENT**, **VTHTEXT**, and so forth).
- **pdwFileId**: Pointer to a **DWORD** that receives a file identification number for the file. These numbers are defined in `sccfi.h`.

**Return Value**

- **DAERR\_OK**: Returned if DAGetFileId was successful. Otherwise, one of the other **DAERR\_** values in `sccda.h` or one of the **SCCERR\_** values in `sccerr.h` is returned.

## 4.10 DAGetFileIdEx

This function allows the developer to retrieve the format of the file based on the technology's content-based file identification process. This can be used to make intelligent decisions about how to process the file and to give the user feedback about the format of the file they are working with. This function has all the functionality of **DAGetFileID** and adds the ability to return the raw **FI** value; in other words, the value returned by normal **FI**, without applying the **FallbackFI** setting.

**Prototype**

```
DAERR DAGetFileIdEx(
    VTHDOC      hDoc,
    VTLPDWORD   pdwFileId,
    VTDWORD     dwFlags);
```

**Parameters**

- **hDoc**: Identifier of open document. May be a **VTHDOC** returned by the **DAOpenDocument** function, or the subhandle returned by the **DAOpenDocument** or **DAOpenTreeRecord** functions (**VTHEXPORT**, **VTHCONTENT**, **VTHTEXT**, and so forth).

- `pdwFileId`: Pointer to a DWORD that receives a file identification number for the file. These numbers are defined in `sccfi.h`.
- `dwFlags`: DWORD that allows user to request specific behavior.
  - `DA_FILEINFO_RAWFI`: This flag tells `DAGetFileIdEx()` to return the result of the File Identification operation before Extended File Ident. is performed and without applying the `FallbackFI` value.

### Return Value

- `DAERR_OK`: Returned if `DAGetFileIdEx` was successful. Otherwise, one of the other `DAERR_` values in `sccda.h` or one of the `SCCERR_` values in `sccerr.h` is returned. See the following tables for examples of expected output depending on the value of various options.

#### Values with RAWFI turned off

Input file type	ExtendedFI	FallbackID	DAGetFileId	DAGetFileIdEx
true binary	off	fallback value	fallback value	fallback value
true binary	on	fallback value	fallback value	fallback value
true text	off	fallback value	fallback value	fallback value
true text	on	fallback value	40XX	40XX

#### Values with RAWFI turned on

Input file type	ExtendedFI	FallbackID	DAGetFileId	DAGetFileIdEx
true binary	off	fallback value	fallback value	1999
true binary	on	fallback value	fallback value	1999
true text	off	fallback value	fallback value	1999
true text	on	fallback value	40XX	1999

## 4.11 DAGetErrorString

This function returns to the developer a string describing the input error code. If the error string returned does not fit the buffer provided, it is truncated.

```
VTVOID DAGetErrorString(
    DAERR      deError,
    VTLPVOID   pBuffer,
    VTDWORD    dwBufSize);
```

### Parameters

- `Error`: Error code passed in by the developer for which an error message is to be returned.
- `pBuffer`: This buffer is allocated by the caller and is filled in with the error message by this routine. The error message will be a NULL-terminated string.
- `dwBufSize`: Size of what `pBuffer` points to in bytes.

### Return Value

- none

## 4.12 DAGetObjectInfo

This function returns information about the document or object pointed to by `hDoc`. The object may be an embedded object, a linked object, or a compressed file.

```
DAERR DAGetObjectInfo(
    VTHDOC      hDoc,
    VTDWORD     dwInfoId,
    VTLPVOID    pInfo);
```

### Parameters

- `hDoc`: The handle returned by `DAOpenDocument`.
- `dwInfoId`

The identifier of the requested information. Can be any of the following values:

- `DAOBJECT_NAME_A`: Retrieves the name of the object, in 8-bit characters. `pInfo` points to a buffer of size `DA_PATHSIZE`.
- `DAOBJECT_NAME_W`: Retrieves the name of the object in Unicode characters. `pInfo` points to a buffer of 16 bit characters of size `DA_PATHSIZE`.
- `DAOBJECT_FORMATID`: Retrieves the file ID of the object. `pInfo` points to a `VTDWORD` value.
- `DAOBJECT_COMPRESSIONTYPE`: Retrieves an identifier of the type of compression used to store the object, if known. `pInfo` points to a `VTDWORD` value.
- `DAOBJECT_FLAGS`: Retrieves a bitfield of flags indicating additional attributes of the object. `pInfo` points to a `VTDWORD` value. Possible flag values include `DAOBJECTFLAG_PARTIALFILE` (would not normally exist outside the source document), `DAOBJECTFLAG_PROTECTEDFILE` (encrypted or password protected), `DAOBJECTFLAG_LINKTOFILE` (indicates that an OLE object is linked to the file and a corresponding file is not found on the host machine), `DAOBJECTFLAG_UNIDENTIFIEDFILE` (indicates that an object could not be identified), and `DAOBJECTFLAG_UNSUPPORTEDCOMP` (compressed with an unsupported compression), and `DAOBJECTFLAG_ARCKNOWNNENCRYPT` (see note below).
- `pInfo`: Destination of the requested information. The possible types are described in the preceding section about `dwInfoId`.

---

**Note:** `DAOBJECTFLAG_ARCKNOWNNENCRYPT` indicates that the object is protected by a known encryption. It can be accessed after the correct credentials (password and/or Lotus Notes id file) are provided through the File Access Callback. For more information, see [DASetFileAccessCallback](#).

---

### Return Values

- `DAERR_OK`: Returned if the save was successful. Otherwise, one of the other `DAERR_` values in `sccda.h` or one of the `SCCERR_` values in `sccerr.h` is returned.

## 4.13 DAGetTreeCount

This function is called to retrieve the number of records in an archive file.

```
DAERR DAGetTreeCount(  
    VTHDOC      hDoc,  
    VTLPDWORD   lpRecordCount);
```

### Parameters

- **hDoc:** Identifier of open document. May be a VTHDOC returned by the DAOpenDocument function, or the subhandle returned by any of the DAOpenDocument or DAOpenTreeRecord functions (VTHCONTENT, VTHTEXT, and so forth).
- **lpRecordCount:** A pointer to a VTLPDWORD that will be filled with the number of stored archive records.

### Return Value

- **DAERR\_OK:** DAGetTreeCount was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- **DAERR\_BADPARAM:** The selected file does not contain an archive section, or the requested record does not exist.

## 4.14 DAGetTreeRecord

This function is called to retrieve information about a record in an archive file.

```
DAERR DAGetTreeRecord(  
    VTHDOC      hDoc,  
    PSCCDATREENODE pTreeNode);
```

### Parameters

- **hDoc:** Identifier of open document. May be a VTHDOC returned by the DAOpenDocument function, or the subhandle by any of the DAOpenDocument or DAOpenTreeRecord functions (VTHCONTENT, VTHTEXT, and so forth).
- **pTreeNode:** A pointer to a PSCCDATREENODE structure that will be filled with information about the selected record.

### Return Values

- **DAERR\_OK:** DAGetTreeRecord was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- **DAERR\_BADPARAM:** The selected file does not contain an archive section, or the requested record does not exist.
- **DAERR\_EMPTYFILE:** Empty file.
- **DAERR\_PROTECTEDFILE:** Password protected or encrypted file.
- **DAERR\_SUPFILEOPENFAILS:** Supplementary file open failed.
- **DAERR\_FILTERNOTAVAIL:** The file's type is known, but the appropriate filter is not available.
- **DAERR\_FILTERLOADFAILED:** An error occurred during the initialization of the appropriate filter.



### 4.14.1 SCCDATREENODE Structure

This structure is passed by the OEM through the DAGetTreeRecord function. The structure is defined in sccda as follows:

```
typedef struct SCCDATREENODEtag{
    VTDWORD    dwSize;
    VTDWORD    dwNode;
    VTBYTE     szName[1024];
    VTDWORD    dwFileSize;
    VTDWORD    dwTime;
    VTDWORD    dwFlags;
    VTDWORD    dwCharSet;
} SCCDATREENODE, *PSCCDATREENODE;
```

#### Parameters

- dwSize: Must be set by the OEM to sizeof(SCCDATREENODE).
- dwNode: The number of the record to retrieve information about.
- szName: A buffer to hold the name of the record.
- dwFileSize: Returns the file size, in bytes, of the requested record.
- dwTime: Returns the timestamp of the requested record, in MS-DOS time.
- dwFlags: Returns additional information about the node. It can be a combination of the following:
  - SCCDA\_TREENODEFLAG\_FOLDER: Indicating that the selected node is a folder and not a file.
  - SCCDA\_TREENODEFLAG\_SELECTED: Indicating that the node is selected.
  - SCCDA\_TREENODEFLAG\_FOCUS: Indicating that the node has focus.
- dwCharSet: Returns the SO\_\* (charsets.h) character set of the characters in szName. The output character set is either the default native environment character set or Unicode if the SCCID\_SYSTEMFLAGS is set to SCCVW\_SYSTEM\_UNICODE.

## 4.15 DAOpenTreeRecord

This function is called to open a record within an archive file and make it accessible by one or more of the data access technologies.

```
DAERR DAOpenTreeRecord(
    VTHDOC    hDoc,
    VTLPHDOC  lphDoc,
    VTDWORD   dwRecord);
```

lphDoc is *not* a file handle.

#### Parameters

- hDoc: Identifier of open document. May be a VTHDOC returned by the DAOpenDocument function, or the subhandle returned by the DAOpenDocument or DAOpenTreeRecord functions (VTHCONTENT, VTHTEXT, and so forth).
- lphDoc: Pointer to a handle that will be filled with a value that uniquely identifies the document to data access. The developer will use this handle in subsequent calls to data access to identify this particular document.

- dwRecord: The record in the archive file to be opened.

**Return Value**

- DAERR\_OK: Returned if DAOpenTreeRecord was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.16 DAOpenRandomTreeRecord

This function is called to open a record within an archive file and make it accessible by one or more of the data access technologies. It is similar to DAOpenTreeRecord, except that instead of reading the data for all nodes in the archive in a sequential order, this function will only read the data for the requested nodes from the archive. To use this function, you must first process the archive with Content Access or Search Export and save the Node Locator data for later use in this function.

```
DAERR DAOpenRandomTreeRecord(  
    VTHDOC      hDoc,  
    VTLPHDOC    lphDoc,  
    SOTREENODELOCATOR sTreeNodeLocator )
```

lphDoc is not a file handle.

**Parameters**

- hDoc: Identifier of open document. This hDoc must come from an archive document opened with DAOpenDocument with the flag DAOPENDOCUMENT\_ARCHIVEONLYMODE set.
- lphDoc: Pointer to a handle that will be filled with a value that uniquely identifies the document to data access. The developer will use this handle in subsequent calls to data access to identify this particular document.
- sTreeNodeLocator: An SOTREENODELOCATOR structure which contains data identifying the desired node. This data should come from a previous conversion of the archive document using Content Access or Search Export.

**Return Value**

- DAERR\_OK: Returned if DAOpenRandomTreeRecord was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

### 4.16.1 DATREENODELOCATOR

```
typedef struct DATREENODELOCATORtag  
{  
    VTDWORD dwSize; /* size of this structure */  
    VTDWORD dwSpecialFlag; /* special flags coming from CA or SX */  
    VTDWORD dwData1; /* dwData1 coming from CA or SX */  
    VTDWORD dwData2; /* dwData2 coming from CA or SX */  
}SCCDATREENODELOCATOR, *PSCCDATREENODELOCATOR;
```

### 4.16.2 SCCCA\_TREEENODELOCATOR: Tree Node Locator

This content type contains information to be used in the SOTREENODELOCATOR structure, which is used by [DAOpenRandomTreeRecord](#) and [DASaveRandomTreeRecord](#).

**SCCCA\_TREENODELOCATOR Content Description**

- dwType: SCCCA\_TREENODELOCATOR
- dwSubType: Reserved
- dwData1: SOTREENODELOCATOR.dwSpecialFlags
- dwData2: SOTREENODELOCATOR.dwData1
- dwData3: SOTREENODELOCATOR.dwData2
- dwData4: Reserved
- pDataBuf: Not used

## 4.17 DASaveInputObject

This function saves a copy of the document or object pointed to by hDoc. The object may be an embedded object, a linked object or a compressed file.

---

**Note:** Some file formats store only partial files as embedded objects. Outside In will not be able to create readable files from these objects. It is recommended that you use DAGetObjectInfo with dwInfold set to DAOBJECT\_FLAGS to discern which objects Outside In will be able to successfully extract.

---

```
DAERR DASaveInputObject(
    VTHDOC      hDoc,
    VTDWORD     dwSpecType,
    VTLPVOID     pSpec,
    VTDWORD     dwFlags);
```

**Parameters**

- hDoc: The handle returned by DAOpenDocument.
- dwSpecType: IOTYPE of data pointed to by pSpec.
- pSpec: File location specification.
- dwFlags: Currently not used. Should be set to 0.

**Return Values**

- DAERR\_OK: Returned if the save was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.18 DASaveTreeRecord

This function is called to extract a record in an archive file to disk.

```
DAERR DASaveTreeRecord(
    VTHDOC      hDoc,
    VTDWORD     dwRecord,
    VTDWORD     dwSpecType,
    VTLPVOID     pSpec,
    VTDWORD     dwFlags);
```

**Parameters**

- **hDoc**: Handle that uniquely identifies the document to data access. NOTE: This is *not* an operating system file handle.
- **dwRecord**: The record in the archive file to be extracted.
- **dwSpecType**: Describes the contents of **pSpec**. Together, **dwSpecType** and **pSpec** describe the location of the source file to which the file will be extracted. Must be one of the following values:
  - **IOTYPE\_ANSIPATH**: Windows only. **pSpec** points to a NULL-terminated full path name using the ANSI character set and FAT 8.3 (Win16) or NTFS (Win32 and Win64) filename conventions.
  - **IOTYPE\_UNICODEPATH**: Windows only. **pSpec** points to a NULL-terminated full path name using the Unicode character set and NTFS (Win32 and Win64) file name conventions.
  - **IOTYPE\_UNIXPATH**: X Windows on UNIX platforms only. **pSpec** points to a NULL-terminated full path name using the system default character set and UNIX path conventions.
- **pSpec**: File location specification.
- **dwFlags**: Currently not used. Should be set to 0.

**Return Values**

- **DAERR\_OK**: Returned if the save was successful. Otherwise, one of the other **DAERR\_** values in `scda.h` or one of the **SCCERR\_** values in `scerr.h` is returned.
- **DAERR\_UNSUPPORTEDCOMP**: Unsupported Compression Encountered.
- **DAERR\_PROTECTEDFILE**: The file is encrypted.
- **DAERR\_BADPARAM**: The request option is invalid. The record is possibly a directory.

Otherwise, one of the other **DAERR\_** values in `scda.h` is returned.

---

**Note:** Currently, only extracting a single file is supported. There is a known limitation where files in a Microsoft Binder file cannot be extracted.

---

## 4.19 DASaveRandomTreeRecord

This function is called to extract a record in an archive file to disk. It is similar to `DASaveTreeRecord`, except that instead of reading the data for all nodes in the archive in a sequential order, this function will only read the data for the requested nodes from the archive. To use this function, you must first process the archive with Content Access or Search Export and save the Node Locator data for later use in this function.

```
DAERR DASaveRandomTreeRecord(  
    VTHDOC          hDoc,  
    SOTREENODELOCATOR sTreeNodeLocator,  
    VTDWORD         dwSpecType,  
    VTLPOVOID       pSpec,  
    VTDWORD         dwFlags)
```

**Parameters**

- **hDoc**: Identifier of open document. This hDoc must come from an archive document opened with `DAOpenDocument` with the flag `DAOPENDOCUMENT_ARCHIVEONLYMODE` set.
- **sTreeNodeLocator**: An `SOTREENODELOCATOR` structure which contains data identifying the desired node. This data should come from a previous conversion of the archive document using Content Access or Search Export.
- **dwSpecType**: Describes the contents of `pSpec`. Together, `dwSpecType` and `pSpec` describe the location of the source file to which the file will be extracted. Must be one of the following values:
  - `IOTYPE_ANSIPATH`: Windows only. `pSpec` points to a NULL-terminated full path name using the ANSI character set and FAT 8.3 (Win16) or NTFS (Win32 and Win64) filename conventions.
  - `IOTYPE_UNICODEPATH`: Windows only. `pSpec` points to a NULL-terminated full path name using the Unicode character set and NTFS (Win32 and Win64) file name conventions.
  - `IOTYPE_UNIXPATH`: X Windows on UNIX platforms only. `pSpec` points to a NULL-terminated full path name using the system default character set and UNIX path conventions.
- **pSpec**: File location specification
- **dwFlags**: Currently not used. Should be set to 0.

**Return Value**

- **DAERR\_OK**: Returned if `DASaveTreeRecord` was successful. Otherwise, one of the other `DAERR_` values in `sccda.h` or one of the `SCCERR_` values in `sccerr.h` is returned.

**4.19.1 DATREENODELOCATOR**

```
typedef struct DATREENODELOCATORtag
{
    VTDWORD dwSize; /* size of this structure */
    VTDWORD dwSpecialFlag; /* special flags coming from CA or SX */
    VTDWORD dwData1; /* dwData1 coming from CA or SX */
    VTDWORD dwData2; /* dwData2 coming from CA or SX */
}SCCDATREENODELOCATOR, *PSCCDATREENODELOCATOR;
```

**4.19.2 SCCCA\_TREENODELOCATOR: Tree Node Locator**

This content type contains information to be used in the `SOTREENODELOCATOR` structure, which is used by [DAOpenRandomTreeRecord](#) and [DASaveRandomTreeRecord](#).

**SCCCA\_TREENODELOCATOR Content Description**

- **dwType**: `SCCCA_TREENODELOCATOR`
- **dwSubType**: Reserved
- **dwData1**: `SOTREENODELOCATOR.dwSpecialFlags`
- **dwData2**: `SOTREENODELOCATOR.dwData1`
- **dwData3**: `SOTREENODELOCATOR.dwData2`

- dwData4: Reserved
- pDataBuf: Not used

## 4.20 DACloseTreeRecord

This function is called to close an open record file handle.

```
DAERR DACloseTreeRecord(  
    VTHDOC      hDoc);
```

### Parameters

- hDoc: Identifier of open record document.

### Return Value

- DAERR\_OK: Returned if DACloseTreeRecord was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.21 DASETSTATCALLBACK

This function sets up a callback that the technology will periodically call into to verify that the file is still being processed. The customer can use this with a monitoring process to help identify files that may be hung. Since this function will be called more frequently than other callbacks, it is implemented as a separate function.

### Use of the Status Callback Function

An application's status callback function will be called periodically by Outside In to provide a status message. Currently, the only status message defined is OIT\_STATUS\_WORKING, which provides a "sign of life" that can be used during unusually long processing operations to verify that Outside In has not stopped working. If the application decides that it would not like to continue processing the current document, it may use the return value from this function to tell Outside In to abort.

The status callback function has two return values defined:

- OIT\_STATUS\_CONTINUE: Tells Outside In to continue processing the current document.
- OIT\_STATUS\_ABORT: Tells Outside In to stop processing the current document.

The following is an example of a minimal status callback function.

```
VTDWORD MyStatusCallback( VTHANDLE hUnique, VTDWORD dwID, VTSYSVAL  
pCallbackData, VTSYSVAL pAppData)  
{  
    if(dwID == OIT_STATUS_WORKING)  
    {  
        if( checkNeedToAbort( pAppData ) )  
            return (OIT_STATUS_ABORT);  
    }  
  
    return (OIT_STATUS_CONTINUE);  
}
```

**Prototype**

```
DAERR DASetStatCallback(DASTATCALLBACKFN pCallback,
                        VTHANDLE hUnique,
                        VTLPVOID pAppData)
```

**Parameters**

- pCallback: Pointer to the callback function.
- dwID: Handle that indicates the callback status.
  - OIT\_STATUS\_WORKING
  - OIT\_STATUS\_CONTINUE
  - OIT\_STATUS\_ABORT
- pCallbackData: Currently always NULL

**Return Values**

- DAERR\_OK: If successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

## 4.22 DASetFileAccessCallback

This function sets up a callback that the technology will call into to request information required to open an input file. This information may be the password of the file or a support file location.

**Use of the File Access Callback**

When the technology encounters a file that requires additional information to access its contents, the application's callback function will be called for this information. Currently, only two different forms of information will be requested: the password of a document, or the file used by Lotus Notes to authenticate the user information.

The status callback function has two return values defined:

- SCCERR\_OK: Tells Outside In that the requested information is provided.
- SCCERR\_CANCEL: Tells Outside In that the requested information is not available.

This function will be repeatedly called if the information provided is not valid (such as the wrong password). It is the responsibility of the application to provide the correct information or return SCCERR\_CANCEL.

**Prototype**

```
DAERR DASetFileAccessCallback (DAFILEACCESSCALLBACKFN pCallback);
```

**Parameters**

- pCallback: Pointer to the callback function.

**Return Values**

- DAERR\_OK: If successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.

The callback function should be of type DAFILEACCESSCALLBACKFN. This function has the following signature:

```
typedef VTDWORD (* DAFILEACCESSCALLBACKFN)(VTDWORD dwID, VTSYSVAL pRequestData,  
VTSYSVAL pReturnData, VTDWORD dwReturnDataSize);
```

- dwID – ID of information requested:
  - OIT\_FILEACCESS\_PASSWORD – Requesting the password of the file
  - OIT\_FILEACCESS\_NOTESID – Requesting the Notes ID file location

- pRequestData – Information about the file.

```
typedef struct {  
    VTDWORD    dwSize;           /* size of this structure */  
    VTWORD     wFIId;           /* FI id of reference file */  
    VTDWORD     dwSpecType;      /* file spec type */  
    VTVOID      *pSpec;          /* pointer to a file spec */  
    VTDWORD     dwRootSpecType;  /* root file spec type */  
    VTVOID      *pRootSpec;      /* pointer to the root file spec */  
    VTDWORD     dwAttemptNumber; /* The number of times the callback has */  
                                /* already been called for the currently */  
                                /* requested item of information */  
} IOREQUESTDATA, * PIOREQUESTDATA;
```

- pReturnData – Pointer to the buffer to hold the requested information – for OIT\_FILEACCESS\_PASSWORD and OIT\_FILEACCESS\_NOTESID, the buffer is an array of WORD characters.
- dwReturnDataSize – Size of the return buffer.

---

---

**Note:** Not all formats that use passwords are supported. Only Microsoft Office binary (97-2003) and Microsoft Office 2007, Lotus NSF, PDF (with RC4 encryption), Zip (with AES 128 & 256 bit, ZipCrypto) are currently supported.

---

---



---

## Text Access Functions

The Text Access module is required to use these functions.

### 5.1 TAOpenText

TAOpenText is used to initiate text access for a file that has been opened by DAOpenDocument.

#### Prototype

```
DAERR TAOpenText (
    VTHDOC      hDoc,
    VTLPHTTEXT  phText )
```

phContent is *not* a file handle.

#### Parameters

- hDoc: A handle that identifies the document, created by DAOpenDocument.
- phText: Pointer to a handle that will receive a value uniquely identifying the document to the Text Access routines. If the function fails, this value will be set to VTHDOC\_INVALID.

#### Return Values

- DAERR\_OK: Open was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.
- DAERR\_EMPTYFILE: Empty file.
- DAERR\_PROTECTEDFILE: Password protected or encrypted file.
- DAERR\_SUPFILEOPENFAILS: Supplementary file open failed.
- DAERR\_FILTERNOTAVAIL: The file's type is known, but the appropriate filter is not available.
- DAERR\_FILTERLOADFAILED: An error occurred during the initialization of the appropriate filter.

### 5.2 TACloseText

TACloseText is called to terminate text access for a file.

### Prototype

```
DAERR TACloseText(  
    VTHTEXT    hText )
```

### Parameters

- hText: Text Access handle for the document. Must be a handle returned by the TAOpenText function.

### Return Values

- DAERR\_OK: Close was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.

## 5.3 TARadFirst

This function is called to set the read pointer to the beginning of the document and to retrieve the first block of text.

### Prototype

```
DAERR TARadFirst(  
    VTHTEXT    hText,  
    VTLPBYTE   pTextBuf,  
    VTDWORD    dwBufSize,  
    VTLPDWORD  pBufCount )
```

Each piece of content has a type and a subtype. Based on the type and subtype, the content is described by using up to four VTDWORDS and a data buffer provided by the caller. The hText, pTextBuf, dwBufSize, and pBufCount elements of this structure should be filled by the caller before calling TARadNext or TARadFirst.

### Parameters

- hText: Text Access handle for the document. Must be a handle returned by the TAOpenText function.
- pTextBuf: Pointer to a buffer to receive the first block of text. NULL characters are included in the text buffer to act as fillers for text which was in the original file but is not part of the document body (revision deletions and document properties). Special characters are manufactured by the technology due to special formatting attributes. For more information, see [Section 5.4, "TARadNext."](#)
- dwBufSize: Size of the buffer pointed to by pTextBuf.
- pBufCount: Pointer to a DWORD that will receive the actual size of the data copied into pTextBuf. Note that for DBCS and Unicode character sets, this will not necessarily be the character count.

### Return Values

- DAERR\_OK: The read was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.

## 5.4 TARReadNext

TARReadNext is called to retrieve the next block of text from the file, beginning at the location where the last call to TARReadNext or TARReadFirst ended.

### Prototype

```
DAERR TARReadNext (
    VTHTEXT      hText,
    VTLPBYTE     pTextBuf,
    VTDWORD      dwBufSize,
    VTLPDWORD    pBufCount )
```

Each piece of content has a type and a subtype. Based on the type and subtype, the content is described by using up to four VTDWORDS and a data buffer provided by the caller. The hText, pTextBuf, dwBufSize, and pBufCount elements of this structure should be filled by the caller before calling TARReadNext or TARReadFirst.

### Parameters

- hText: Text Access handle for the document. Must be a handle returned by the TAOpenText function.
- pTextBuf: Pointer to a buffer to receive the block of text. NULL characters are included in the text buffer to act as fillers for text which was in the original file but is not part of the document body (revision deletions and document properties). Special characters are manufactured by the technology due to special formatting attributes.
- dwBufSize: This is the size of the buffer pointed to by pTextBuf.
- pBufCount: Pointer to a DWORD that will receive the actual size of the data copied into pTextBuf. Note that for DBCS and Unicode character sets, this will not necessarily be the character count.

### Return Values

- DAERR\_OK: The read was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_EOF: Read was successful, and the end of the file was encountered.
- DAERR\_ABORT: A fatal error has occurred, read process was aborted.

### Special Text Character Substitutions

- Email Delimiter: 0x09
- End of Database Record: 0x0A
- End of File: 0x0D
- End of Paragraph: 0x0D
- End of Table Cell: 0x0D
- End of Table Row: 0x0D
- Hard Hyphen: 0x2D
- Hard Line Break: 0x0A
- Hard Page Break: 0x0C
- Hard Space: 0x20

- Section Separator: 0x0D
- Syllable Hyphen: 0x2D
- Tab: 0x09
- Word Delimiter: 0x20

---

## Content Access Functions

The Content Access module is required to use these functions.

### 6.1 CAOpenContent

CAOpenContent is used to initiate content access for a file that has been opened by DAOpenDocument.

#### Prototype

```
DAERR CAOpenContent (
    VTHDOC      hDoc;
    VTLPHCONTENT phContent;
)
```

phContent is *not* a file handle.

#### Parameters

- hDoc: A handle that identifies the document, created by DAOpenDocument.
- phContent: Pointer to a handle that will receive a value uniquely identifying the document to the Content Access routines. If the function fails, this value will be set to VTHDOC\_INVALID.

#### Return Values

- DAERR\_OK: Open was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.
- DAERR\_EMPTYFILE: Empty file.
- DAERR\_PROTECTEDFILE: Password protected or encrypted file.
- DAERR\_SUPFILEOPENFAILS: Supplementary file open failed.
- DAERR\_FILTERNOTAVAIL: The file's type is known, but the appropriate filter is not available.
- DAERR\_FILTERLOADFAILED: An error occurred during the initialization of the appropriate filter.

### 6.2 CACloseContent

CACloseContent is called to terminate content access for a file.

**Prototype**

```
DAERR CACloseContent(  
    VTHCONTENT    hContent;  
)
```

**Parameters**

- hContent: Content Access handle for the document. Must be a handle returned by the CAOpenContent function.

**Return Values**

- DAERR\_OK: Close was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.

## 6.3 CReadFirst

This function is called to set the read pointer to the beginning of the document content and to obtain the file identification property for the document.

**Prototype**

```
DAERR CReadFirst(  
    VTHCONTENT    hContent;  
    PSCCCAGETCONTENT pGetContent;  
)
```

**Parameters**

- hContent: Content Access handle for the document. Must be a handle returned by the CAOpenContent function.
- pGetContent: Pointer to a structure of type SCCCAGETCONTENT (see [Section 6.4.1, "SCCCAGETCONTENT Structure"](#)). CReadFirst will always fill this structure with the file identification property.

**Return Values**

- DAERR\_OK: Read was successful. Otherwise, one of the other DAERR\_ values in sccda.h or one of the SCCERR\_ values in sccerr.h is returned.
- DAERR\_BADPARAM: One of the function parameters was invalid.

## 6.4 CReadNext

CReadNext is called to retrieve text and properties from a file, beginning at the location where the last content was provided.

**Prototype**

```
DAERR CReadNext(  
    VTHCONTENT    hContent;  
    PSCCCAGETCONTENT pGetContent;  
)
```

**Parameters**

- hContent: Content Access handle for the document. Must be a handle returned by the CAOpenContent function.

- `pGetContent`: Pointer to a structure of type `SCCCAGETCONTENT` (see [Section 6.4.1, "SCCCAGETCONTENT Structure"](#)).

### Return Values

- `DAERR_OK`: Read was successful. Otherwise, one of the other `DAERR_` values in `sccda.h` or one of the `SCCERR_` values in `sccerr.h` is returned.
- `DAERR_EOF`: Read was successful, and the end of the file was encountered.
- `DAERR_ABORT`: A fatal error has occurred, read process was aborted.

## 6.4.1 SCCCAGETCONTENT Structure

```
typedef struct SCCCAGETCONTENTtag
{
    VTDWORD      dwStructSize;
    VTDWORD      dwFlags;
    VTDWORD      dwMaxBufSize;
    VTVOID       * pDataBuf;
    VTDWORD      dwType;
    VTDWORD      dwSubType;
    VTDWORD      dwData1;
    VTDWORD      dwData2;
    VTDWORD      dwData3;
    VTDWORD      dwData4;
    VTDWORD      dwDataBufSize;
} SCCCAGETCONTENT, * PSCCCAGETCONTENT;
```

Each piece of content has a type and a subtype. Based on the type and subtype, the content is described by using up to four `VTDWORDS` and a data buffer provided by the caller. The `dwStructSize`, `dwFlags`, `pDataBuf` and `dwMaxBufSize` elements of this structure should be filled by the caller before calling `CAREadNext` or `CAREadFirst`.

- `dwStructSize`: Initialized by caller to `sizeof(SCCCAGETCONTENT)`.
- `dwFlags`: Set by caller. Currently undefined, must be set to 0.
- `dwMaxBufSize`: Initialized by caller to the size of the buffer pointed to by `pDataBuf`.
- `pDataBuf`: This pointer must be set by the caller to a buffer at least 1K in size and must be properly byte-aligned (4 bytes). This buffer will be filled with content information based on `dwType`.
- `dwType`: Returns one of the following values (For detailed descriptions of the content types, see [Chapter 7, "Content Description"](#)):
  - `SCCCA_ANNOTATION`: Marks the location of an annotation or sub-document.
  - `SCCCA_BEGINTAG`: Marks the beginning of a tagged section of the document
  - `SCCCA_BREAK`: Signals the end of document properties
  - `SCCCA_ENDTAG`: Marks the end of a tagged section of the document
  - `SCCCA_FILEPROPERTY`: File identification information
  - `SCCCA_GENERATED`: Text generated from non-character data
  - `SCCCA_OBJECT`: Embedded object information
  - `SCCCA_SHEET`: The name of a sheet in a spreadsheet or presentation

- SCCCA\_STYLECHANGE: Indicates a change in style information
- SCCCA\_TEXT: Normal stream text
- SCCCA\_TREENODELOCATOR: Used by [DAOpenRandomTreeRecord](#) and [DASaveRandomTreeRecord](#).
- dwSubType Returns additional information based on dwType. Here are some valid subtypes:
  - SCCCA\_ANNOTATION: Subtype are values like SCCCA\_ANNOTATION\_FOOTNOTE or SCCCA\_ANNOTATION\_ENDNOTE. dwData1 links to the corresponding SCCCA\_BEGINTAG.
  - SCCCA\_HIDDEN: A valid subtype for the SCCCA\_TEXT type representing hidden text.
  - SCCCA\_FRAME\_EX: A valid subtype for the SCCCA\_BEGINTAG and SCCCA\_ENDTAG types representing extended frames.
  - SCCCA\_LINKEDOBJECT: A valid subtype for the SCCCA\_BEGINTAG and SCCCA\_ENDTAG types representing an object accessible via a link. When dwSubType equals SCCCA\_LINKEDOBJECT, dwData1, dwData2, dwData3 and dwData4 will contain values that are used to locate the object.
  - SCCCA\_OCE: A valid subtype for the SCCCA\_STYLECHANGE type, indicating a change in the character set in the original document.
- dwData*n*: Return additional information based on dwType and dwSubType. For example, dwData2 returns the input file's initial character set.
- dwDataBufSize: Returns the actual size of the data placed in the buffer pointed to by pDataBuf.



---

## Content Description

This chapter discusses tagged content and other content topics.

### 7.1 SCCCA\_BEGINTAG/SCCCA\_ENDTAG: Tagged Content

The SCCCA\_BEGINTAG and SCCCA\_ENDTAG content types are used to tag or delimit other content for a particular purpose. This can be especially useful when searching for specific document property values like the author or title of a document. It can also be used to separate subdocument text like headers, footers, and footnotes from the main document text. Tagged text may be nested inside other tagged text, and tags may overlap each other.

Though most tag types are not particularly useful to developers, the Data Access technology provides all of the tag types rather than make a judgment as to usability. Each is briefly described below.

#### 7.1.1 SCCCA\_BEGINTAG Content Description

This section lists the applicable parameters and corresponding values.

- dwType
  - SCCCA\_BEGINTAG: Beginning of tagged content
  - SCCCA\_ENDTAG: End of tagged content
- dwSubType: Tag type - see [Section 7.1.2, "Tag Types"](#)
- dwData1: Additional ID - see [Section 7.1.3, "Document Property IDs,"](#) or [Section 7.1.5, "Mail Field IDs"](#)
- dwData2: Not used
- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: Not used

#### 7.1.2 Tag Types

This section lists the applicable values and corresponding descriptions.

- SCCCA\_ALTFONTDATA: Reserved
- SCCCA\_ANNOTATIONREFERENCE: Tags content that references an annotation
- SCCCA\_BOOKMARK: Delimits content tagged as a bookmark

- SCCCA\_CAPTIONTEXT: Tags content that is used as a caption on objects such as tables, equations and figures
- SCCCA\_CHARACTER: Reserved
- SCCCA\_COMPILEDFIELD: Tags content resulting from an application compiling a field code such as a date. The lack of consistent support by applications for this field makes it unreliable as a search property.
- SCCCA\_CONDITIONALSTYLE: Reserved
- SCCCA\_COUNTERFORMAT: Reserved
- SCCCA\_CUSTOMDATAFORMAT: Reserved
- SCCCA\_DATEDEFINITION: Reserved
- SCCCA\_DIAGRAM: Reserved
- SCCCA\_DIAGRAM\_\*: Reserved
- SCCCA\_DOCUMENTPROPERTY: Tags document property content - see [Section 7.1.3, "Document Property IDs"](#)
- SCCCA\_DOCUMENTPROPERTYNAME: Name of a user-defined document property (SCCCA\_USERDEFINEDPROP)
- SCCCA\_EMAILFIELD: Tags fields associated with email formats - see [Section 7.1.5, "Mail Field IDs"](#)
- SCCCA\_EMAILFIELDNAME: Tags the name of a non-standard email field.
- SCCCA\_EMAILTABLE: Table of email fields
- SCCCA\_ENDNOTEREFERENCE: Tags content that references an endnote
- SCCCA\_FONTANDGLYPHDATA: Tags content that references font or glyph data
- SCCCA\_FOOTER: Delimits content tagged as footer
- SCCCA\_FOOTNOTEREFERENCE: Tags content that references a footnote
- SCCCA\_FRAME: Tags content stored within a frame
- SCCCA\_FRAME\_EX: Tags content that references extended frames
- SCCCA\_GENERATEDFIELD: Reserved
- SCCCA\_GENERATOR: Reserved
- SCCCA\_HEADER: Delimits content tagged as header
- SCCCA\_HYPERLINK: Delimits content tagged as a hypertext link
- SCCCA\_INDEX: Reserved
- SCCCA\_INDEXENTRY: Delimits content that should be placed in the index
- SCCCA\_INLINEDATAFORMAT: Reserved
- SCCCA\_LINKEDOBJECT: Tags content referencing a linked object
- SCCCA\_LISTENTRY: Reserved
- SCCCA\_MERGEENTRY: Reserved
- SCCCA\_NAMEDCELLRANGE: Reserved
- SCCCA\_REFERENCEDTEXT: Tags text for later reference

- SCCCA\_SLIDENOTES: Tags content stored in speaker/slide notes in a presentation document
- SCCCA\_SSHEADERFOOTER: Tags content that references headers or footers in spreadsheet files
- SCCCA\_STYLE: Delimits a style definition. Styles may contain text, but typically do not.
- SCCCA\_SUBDOCPROPERTY: Tags metadata associated with a subdocument, such as a comment.
- SCCCA\_SUBDOCTEXT: Delimits content stored in subdocuments like headers, footers, frames and notes.
- SCCCA\_TOA: Reserved
- SCCCA\_TOAENTRY: Reserved
- SCCCA\_TOC: Reserved
- SCCCA\_TOCENTRY: Reserved
- SCCCA\_TOF: Reserved
- SCCCA\_VECTORSAVETAG: Reserved
- SCCCA\_XMPDATA: Document properties parsed out of the XMP data
- SCCCA\_XREF: Reserved

When dwSubType is SCCCA\_DOCUMENTPROPERTY, dwData1 will be one of the values listed in the header file `sccca.h`. The following section, Document Property IDs, lists many of the common document property types. Any content generated between the begin and end tag defines the value of the document property.

When dwSubType is SCCCA\_EMAILFIELD, dwData1 will be one of the values in [Section 7.1.5, "Mail Field IDs,"](#) and any content generated between the begin and end tag defines the value of the email field.

### 7.1.3 Document Property IDs

The following is a partial list of document property IDs.

- SCCCA\_ABSTRACT
- SCCCA\_ACCOUNT
- SCCCA\_ADDRESS
- SCCCA\_APPVERSION
- SCCCA\_ATTACHMENTS
- SCCCA\_AUTHORIZATION
- SCCCA\_BACKUPDATE
- SCCCA\_BASEFILELOCATION
- SCCCA\_BILLTO
- SCCCA\_BLINDCOPY
- SCCCA\_CARBONCOPY
- SCCCA\_CATEGORY
- SCCCA\_CHECKEDBY

- SCCCA\_CLIENT
- SCCCA\_COMPANY
- SCCCA\_COMPLETEDDATE
- SCCCA\_COUNTBYTES
- SCCCA\_COUNTCHARS
- SCCCA\_COUNTCHARSWITHSPACES
- SCCCA\_COUNTLINES
- SCCCA\_COUNTMMCLIPS
- SCCCA\_COUNTNOTES
- SCCCA\_COUNTPAGES
- SCCCA\_COUNTPARAS
- SCCCA\_COUNTSLIDES
- SCCCA\_COUNTSLIDESHIDDEN
- SCCCA\_COUNTWORDS
- SCCCA\_CREATIONDATE
- SCCCA\_DEPARTMENT
- SCCCA\_DESTINATION
- SCCCA\_DISPOSITION
- SCCCA\_DIVISION
- SCCCA\_DOCCOMMENT
- SCCCA\_DOCNUMBER
- SCCCA\_DOCTYPE
- SCCCA\_EDITMINUTES
- SCCCA\_EDITOR
- SCCCA\_FORWARDTO
- SCCCA\_GROUP
- SCCCA\_HEADINGPAIRS
- SCCCA\_KEYWORD
- SCCCA\_LANGUAGE
- SCCCA\_LASTPRINTDATE
- SCCCA\_LASTSAVEDATE
- SCCCA\_LASTSAVEDBY
- SCCCA\_LINKSDIRTY
- SCCCA\_MAILSTOP
- SCCCA\_MANAGER
- SCCCA\_MATTER
- SCCCA\_OFFICE

- SCCCA\_OPERATOR
- SCCCA\_OWNER
- SCCCA\_PRESENTATIONFORMAT
- SCCCA\_PRIMARYAUTHOR
- SCCCA\_PROJECT
- SCCCA\_PUBLISHER
- SCCCA\_PURPOSE
- SCCCA\_RECEIVEDFROM
- SCCCA\_RECORDEDBY
- SCCCA\_RECORDEDDATE
- SCCCA\_REFERENCE
- SCCCA\_REVISIONDATE
- SCCCA\_REVISIONNOTES
- SCCCA\_REVISIONNUMBER
- SCCCA\_SCALECROP
- SCCCA\_SECONDARYAUTHOR
- SCCCA\_SECTION
- SCCCA\_SECURITY
- SCCCA\_SOURCE
- SCCCA\_STATUS
- SCCCA\_SYSTEM\_FILECREATED
- SCCCA\_SYSTEM\_FILEMODIFIED
- SCCCA\_SYSTEM\_FILESIZE
- SCCCA\_SUBJECT
- SCCCA\_TITLE
- SCCCA\_TITLEOFFPARTS
- SCCCA\_TYPIST
- SCCCA\_USERDEFINEDPROP
- SCCCA\_VERSIONDATE
- SCCCA\_VERSIONNOTES
- SCCCA\_VERSIONNUMBER

---

**Note:** Document Properties with IDs of SCCCA\_USERDEFINEDPROP or above are user-defined properties.

---

#### 7.1.4 SCCCA\_SUBDOCPROPERTY Document Properties

The following values are properties of SCCCA\_SUBDOCPROPERTY:

- SCCCA\_SUBDOC\_AUTHOR

- SCCCA\_SUBDOC\_CREATEDATE
- SCCCA\_SUBDOC\_LASTSAVEDATE
- SCCCA\_SUBDOC\_TITLE
- SCCCA\_SUBDOC\_NOTES
- SCCCA\_SUBDOC\_AUTHORSHORT

### 7.1.5 Mail Field IDs

This is a partial list of fields found in mail documents and archives.

- SCCCA\_MAIL\_ALTERNATE\_RECIPIENT\_ALLOWED
- SCCCA\_MAIL\_ATTACHMENT
- SCCCA\_MAIL\_ATTENDEES
- SCCCA\_MAIL\_ATTR\_HIDDEN
- SCCCA\_MAIL\_ATTR\_READONLY
- SCCCA\_MAIL\_ATTR\_SYSTEM
- SCCCA\_MAIL\_AUTO\_FORWARDED
- SCCCA\_MAIL\_BCC
- SCCCA\_MAIL\_CATEGORIES
- SCCCA\_MAIL\_CC
- SCCCA\_MAIL\_CCME
- SCCCA\_MAIL\_CLIENT\_SUBMIT\_TIME
- SCCCA\_MAIL\_COMPANY
- SCCCA\_MAIL\_CONVERSATION\_INDEX
- SCCCA\_MAIL\_CONVERSATION\_TOPIC
- SCCCA\_MAIL\_CREATION\_TIME
- SCCCA\_MAIL\_CREATOR\_ENTRYID
- SCCCA\_MAIL\_CREATOR\_NAME
- SCCCA\_MAIL\_DEFERRED\_DELIVERY\_TIME
- SCCCA\_MAIL\_DELETE\_AFTER\_SUBMIT
- SCCCA\_MAIL\_EMAIL
- SCCCA\_MAIL\_ENTRYID
- SCCCA\_MAIL\_EXPIRES
- SCCCA\_MAIL\_EXPIRY\_TIME
- SCCCA\_MAIL\_FLAGSTS
- SCCCA\_MAIL\_FROM
- SCCCA\_MAIL\_FULLNAME
- SCCCA\_MAIL\_HOMEPHONE
- SCCCA\_MAIL\_IMPORTANCE

- SCCCA\_MAIL\_INET\_MAIL\_OVERRIDE\_FORMAT
- SCCCA\_MAIL\_INTERNET\_ARTICLE\_NUMBER
- SCCCA\_MAIL\_INTERNET\_CPID
- SCCCA\_MAIL\_INTERNET\_MESSAGE\_ID
- SCCCA\_MAIL\_JOBTITLE
- SCCCA\_MAIL\_LASTMODIFIED
- SCCCA\_MAIL\_LAST\_MODIFIER\_ENTRYID
- SCCCA\_MAIL\_LAST\_MODIFIER\_NAME
- SCCCA\_MAIL\_LATEST\_DELIVERY\_TIME
- SCCCA\_MAIL\_LOCATION
- SCCCA\_MAIL\_MESSAGE\_CLASS
- SCCCA\_MAIL\_MESSAGE\_CODEPAGE
- SCCCA\_MAIL\_MESSAGE\_LOCALE\_ID
- SCCCA\_MAIL\_MESSAGE\_SUBMISSION\_ID
- SCCCA\_MAIL\_MSGFLAG
- SCCCA\_MAIL\_MSG\_EDITOR\_FORMAT
- SCCCA\_MAIL\_NEWSGROUPS
- SCCCA\_MAIL\_NORMALIZED\_SUBJECT
- SCCCA\_MAIL\_NT\_SECURITY\_DESCRIPTOR
- SCCCA\_MAIL\_ORIGINATOR\_DELIVERY\_REPORT\_REQUESTED
- SCCCA\_MAIL\_PRIORITY
- SCCCA\_MAIL\_PROFILE\_CONNECT\_FLAGS
- SCCCA\_MAIL\_RCVD\_BY\_FLAGS
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_ADDRTYPE
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_ENTRYID
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_FLAGS
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_NAME
- SCCCA\_MAIL\_RCVD\_REPRESENTING\_SEARCH\_KEY
- SCCCA\_MAIL\_READ\_RECEIPT\_REQUESTED
- SCCCA\_MAIL\_RECEIVED
- SCCCA\_MAIL\_RECEIVED\_BY\_ADDRTYPE
- SCCCA\_MAIL\_RECEIVED\_BY\_EMAIL\_ADDRESS
- SCCCA\_MAIL\_RECEIVED\_BY\_ENTRYID
- SCCCA\_MAIL\_RECEIVED\_BY\_NAME
- SCCCA\_MAIL\_RECEIVED\_BY\_SEARCH\_KEY
- SCCCA\_MAIL\_RECIPIENT\_REASSIGNMENT\_PROHIBITED

- SCCCA\_MAIL\_REPLY\_REQUESTED
- SCCCA\_MAIL\_REPLY\_TIME
- SCCCA\_MAIL\_REPORT\_TAG
- SCCCA\_MAIL\_RESPONSE\_REQUESTED
- SCCCA\_MAIL\_RTFBODY
- SCCCA\_MAIL\_RTF\_IN\_SYNC
- SCCCA\_MAIL\_RTF\_SYNC\_BODY\_COUNT
- SCCCA\_MAIL\_RTF\_SYNC\_BODY\_CRC
- SCCCA\_MAIL\_RTF\_SYNC\_BODY\_TAG
- SCCCA\_MAIL\_RTF\_SYNC\_PREFIX\_COUNT
- SCCCA\_MAIL\_RTF\_SYNC\_TRAILING\_COUNT
- SCCCA\_MAIL\_SEARCH\_KEY
- SCCCA\_MAIL\_SENDER\_ADDRTYPE
- SCCCA\_MAIL\_SENDER\_EMAIL\_ADDRESS
- SCCCA\_MAIL\_SENDER\_ENTRYID
- SCCCA\_MAIL\_SENDER\_FLAGS
- SCCCA\_MAIL\_SENDER\_NAME
- SCCCA\_MAIL\_SENDER\_SEARCH\_KEY
- SCCCA\_MAIL\_SENSITIVITY
- SCCCA\_MAIL\_SENT\_REPRESENTING\_ADDRTYPE
- SCCCA\_MAIL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS
- SCCCA\_MAIL\_SENT\_REPRESENTING\_ENTRYID
- SCCCA\_MAIL\_SENT\_REPRESENTING\_FLAGS
- SCCCA\_MAIL\_SENT\_REPRESENTING\_NAME
- SCCCA\_MAIL\_SENT\_REPRESENTING\_SEARCH\_KEY
- SCCCA\_MAIL\_SIZE
- SCCCA\_MAIL\_SUBJECT
- SCCCA\_MAIL\_SUBMITTIME
- SCCCA\_MAIL\_TO
- SCCCA\_MAIL\_TRANSPORT\_MESSAGE\_HEADERS
- SCCCA\_MAIL\_TRUST\_SENDER
- SCCCA\_MAIL\_WEBPAGE
- SCCCA\_MAIL\_WORKPHONE

## 7.2 SCCCA\_COMMENTREFERENCE Content Description

A SCCCA\_COMMENTREFERENCE is placed in the actual location of the comment. The body of the comment may appear elsewhere and will be tagged with a SCCCA\_



BEGINTAG of type SCCCA\_SUBDOCTEXT and will have the same Id as the SCCCA\_COMMENTREFERENCE.

- dwType: SCCCA\_COMMENTREFERENCE
- dwSubType: None
- dwData1: Type of the comment reference anchor. SCCCA\_COMMENT\_PARAGRAPH, SCCCA\_COMMENT\_CELL, SCCCA\_COMMENT\_SLIDE, or SCCCA\_COMMENT\_VECTORPAGE.
- dwData2: id of the associated subdoc
- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: Not used

### 7.3 SCCCA\_BREAK: Content Breaks

This content type is used internally, and may be ignored.

### 7.4 SCCCA\_CELL: Cell Boundary

SCCCA\_CELL will appear before the contents of a cell in a spreadsheet or database and will contain coordinates that indicate the starting and ending position of the cell. If the cell isn't merged, then the starting and ending positions will be the same. The content contained by the cell is assumed to end when the next SCCCA\_CELL or SCCCA\_SHEET is output.

#### 7.4.1 SCCCA\_CELL Content Description

- dwType: SCCCA\_CELL
- dwSubType: Not used
- dwData1: The starting row in a numeric format that is 0 based
- dwData2: The starting column in a numeric format that is 0 based
- dwData3: The ending row in a numeric format that is 0 based
- dwData4: The ending column in a numeric format that is 0 based
- pDataBuf: Not used

### 7.5 SCCCA\_FILEPROPERTY: File Property Content

Returns the file identification information for a document. This property is generated by the CReadFirst function.

#### 7.5.1 SCCCA\_FILEPROPERTY Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_FILEPROPERTY
- dwSubType: SCCCA\_FILEID
- dwData1: One of the file identifier values (FI\_\*) defined in sccfi.h
- dwData2: The input file's initial character set

- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: Not used

## 7.6 SCCCA\_GENERATED: Generated Information

Identical to SCCCA\_TEXT, except that the characters come not from the original document, but from some other non-character data (numbers in spreadsheets, dates, and so forth). Because the text is not from the original document, the characters do not contribute toward character counts.

### 7.6.1 SCCCA\_GENERATED Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_GENERATED
- dwSubType: Possible values include the following:
  - SCCCA\_BOOKMARKTEXT: Text for the internal name of the bookmark.
  - SCCCA\_DOCUMENTTEXT: Regular document text is returned with this subtype.
  - SCCCA\_SPECIALTEXT: Used to return text elements that are manufactured by the technology due to special formatting attributes.
  - SCCCA\_REVISIONDELETE: Will be OR-ed with either SCCCA\_DOCUMENTTEXT or SCCCA\_SPECIALTEXT when text has been deleted from the final version of a document as a result of a revision.
  - SCCCA\_URLTEXT: Text for the Link Location part of a URL.
  - SCCCA\_XMPMETADATA: Text from embedded XMP metadata.
- dwData1: Number of characters provided in pDataBuf
- dwData2: Original character set of the text in pDataBuf
- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: Text buffer. Filled with one or more single- or double-byte characters.

## 7.7 SCCCA\_OBJECT: SubObjects

This content type is provided to allow the developer to access the content of SubObjects, like embedded graphics or objects in an archive. The SubObject can then be opened by DAOpenDocument, filling the IOSPECSUBOBJECT or the IOSPECARCHIVEOBJECT parameter with one of the following values:

### 7.7.1 SCCCA\_OBJECT Content Description

- dwType: SCCCA\_OBJECT
- dwSubType: Set to SCCCA\_EMBEDDEDOBJECT (0) if the sub-object is an embedding or is set to the type of node if the object is from an archive. Possible values include the following:
  - SCCCA\_EMBEDDEDOBJECT

- SCCCA\_ARCHIVEITEMCONTAINER
- SCCCA\_COMPRESSEDFILE
- SCCCA\_MESSAGE
- SCCCA\_CONTACT
- SCCCA\_CALENDARENTRY
- SCCCA\_NOTE
- SCCCA\_TASK
- SCCCA\_JOURNALENTY
- SCCCA\_ATTACHMENT
- dwData1: The internal SubObject identifier or a node identifier.
- dwData2: Stream identifier for an alternate graphic.
- dwData3: Stream identifier for an OLE object if one exists. Otherwise, it is CA\_INVALIDITEM.
- dwData4: Object Flags. Currently, 0 or SCCCA\_ENDRECORD
- pDataBuf: Not used

## 7.8 SCCCA\_RECORD: Archive Record

This content is output to allow the customer to easily group fields that appear in an archive or in an email archive. The record is considered to be open until a SCCCA\_OBJECT is encountered with the flag SCCCA\_ENDRECORD set.

### 7.8.1 SCCCA\_RECORD Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_RECORD
- dwSubType: Reserved
- dwData1: Reserved
- dwData2: Reserved
- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: not used

## 7.9 SCCCA\_SHEET: Sheet Names

This content type contains only the sheet name (worksheet in a spreadsheet, slide in presentation, and so forth). This content is *not* optional. It is always created if the information is present. Of course, the client can ignore this text when it is returned.

### 7.9.1 SCCCA\_SHEET Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_SHEET
- dwSubType: Reserved

- dwData1: The length of the name in pDataBuf in characters.
- dwData2: The original character set of the name in pDataBuf.
- dwData3: Reserved
- dwData4: Reserved
- pDataBuf: Points to the sheet name in whatever output character set has been requested.

## 7.10 SCCCA\_STYLECHANGE: Style Information

The SCCCA\_STYLECHANGE content type is used to indicate changes in style information. This style information can be used to delimit particularly interesting content.

### 7.10.1 SCCCA\_STYLECHANGE Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_STYLECHANGE
- dwSubType: Possible values include the following:
  - SCCCA\_PARASTYLE: pDataBuf indicates the name of the style.
  - SCCCA\_HEIGHTANDSPACING: When dwSubType is SCCCA\_HEIGHTANDSPACING, dwData1 can be SCCCA\_HEIGHT (dwData2 represents the new character height), SCCCA\_SPACING (dwData3 represents the new line spacing) or both of these values OR-ed together.
  - SCCCA\_INDENTS: When dwSubType is SCCCA\_INDENTS, dwData1 can be SCCCA\_LEFTINDENT (dwData2 represents the left indent), SCCCA\_RIGHTINDENT (dwData3 represents the right indent), SCCCA\_FIRSTINDENT (dwData4 represents the first line indent), or any of these values OR-ed together.
  - SCCCA\_OCE: This content type provides information about the original charsets of the characters that follow. dwData1 represents the charset as defined in vtchars.h.
- dwData1: Depends on the value of dwSubType.
- dwData2: Depends on the value of dwSubType.
- dwData3: Depends on the value of dwSubType.
- dwData4: Depends on the value of dwSubType.
- pDataBuf: Text buffer. Filled with one or more single- or double-byte characters.
- dwDataBufSize: Size of pDataBuf, in bytes.

## 7.11 SCCCA\_TEXT: Text Content

This content type denotes document text, including special characters such as page breaks and tabs.

The technology guarantees that the text generated by the Content Access technology is identical to the text generated by the Outside In Viewer technology raw-text feature. This allows character counts generated at indexing time using Content Access to be directly mapped to viewer positions at viewing time for search-hit highlighting.

However, Content Access has abilities beyond the raw-text feature of the Viewer, such as the ability to retrieve non-visible text such as document properties and hidden text, and the ability to retrieve text from embedded documents.

When the output character is DBCS or Unicode, the character count will not be the same as the buffer byte count because these character sets may generate more than one byte per character. The byte ordering used for multi-byte character sets such as these will be system-dependent; on a computer using an Intel processor, the low byte will be first.

It is important to note that generated numeric data fields, such as date, time, and spreadsheet numbers, are not included in the content returned by SCCCA\_TEXT. For information on how such text can be returned by Content Access, see [Section 7.6](#), "SCCCA\_GENERATED: Generated Information."

### 7.11.1 SCCCA\_TEXT Content Description

This section lists the applicable parameters and corresponding values.

- dwType: SCCCA\_TEXT
- dwSubType: One of the following values:
  - SCCCA\_DOCUMENTTEXT: Regular document text is returned with this subtype.
  - SCCCA\_SPECIALTEXT: Used to return text elements that are manufactured by the technology due to special formatting attributes.

SCCCA\_DOCUMENTTEXT or SCCCA\_SPECIALTEXT can be optionally OR-ed with any of the following to specify the type of text to be returned:

- SCCCA\_ALLCAPS
- SCCCA\_BOLD
- SCCCA\_DUNDERLINE
- SCCCA\_HIDDEN
- SCCCA\_ITALIC
- SCCCA\_OUTLINE
- SCCCA\_REVISIONDELETE: Text that has been deleted from the final version of a document as a result of a revision.
- SCCCA\_REVISIONADD: Text that has been added to the final version of a document as a result of a revision.
- SCCCA\_SMALLCAPS
- SCCCA\_STRIKEOUT
- SCCCA\_UNDERLINE
- SCCCA\_UNKNOWNMAP: This flag is set when PDF files don't contain a ToUnicode map. This indicates that the mappings may or may not be correct.
- dwData1: Number of characters provided in pDataBuf
- dwData2: Original character set of the text in pDataBuf
- dwData3: Reserved
- dwData4: Reserved

- pDataBuf: Text buffer. Filled with one or more single- or double-byte characters.

### 7.11.2 Special Text Character Substitutions

- Email Delimiter: 0x09
- End of Database Record: 0x0A
- End of File: 0x0D
- End of Paragraph: 0x0D
- End of Table Cell: 0x0D
- End of Table Row: 0x0D
- Hard Hyphen: 0x2D
- Hard Line Break: 0x0A
- Hard Page Break: 0x0C
- Hard Space: 0x20
- Implied Space: 0x20
- Section Separator: 0x0D
- Syllable Hyphen: 0x2D
- Tab: 0x09

## 7.12 SCCCA\_TREENODELOCATOR: Tree Node Locator

This content type contains information to be used in the SOTREENODELOCATOR structure, which is used by [DAOOpenRandomTreeRecord](#) and [DASaveRandomTreeRecord](#).

### 7.12.1 SCCCA\_TREENODELOCATOR Content Description

- dwType: SCCCA\_TREENODELOCATOR
- dwSubType: Reserved
- dwData1: SOTREENODELOCATOR.dwSpecialFlags
- dwData2: SOTREENODELOCATOR.dwData1
- dwData3: SOTREENODELOCATOR.dwData2
- dwData4: Reserved
- pDataBuf: Not used

---

## Redirected IO

Many developers using the earlier versions of this technology expressed a need to read file data from non-file system based sources. For instance, the developer might want to read the file from a database on a server. Perhaps the developer is downloading the file over a slow link, and wants to see the first screen of a document before the download is completed, or only wants to download enough to view the first screen. To address these requests, developers now have total control over access to a file via Outside In's redirected IO mechanism.

### 8.1 Using Redirected IO

A developer can redirect the IO for an input or output file by providing a data structure that contains pointers to custom IO routines for reading and writing. This data structure is passed in place of a typical file specification. The developer must set the `dwSpecType` parameter of the `DAOpenDocument` call to `IOTYPE_REDIRECT` when the `DAOpenDocument` call is sent.

When `dwSpecType` is set this way, the `pSpec` element must contain a pointer to a developer-defined data structure that begins with a `BASEIO` structure (defined in `baseIO.H`). The `BASEIO` structure contains pointers to the basic IO functions for the view window's IO system such as `Read`, `Seek`, `Tell`, and so forth. The developer must initialize these function pointers to their own functions that perform IO tasks. Beyond the `BASEIO` element, the developer may place any data he or she likes. For instance, a developer's structure may be similar to the following:

```
typedef struct MYFILEtag
{
    BASEIO    sBaseIO;        /* must be the first element */
    VTDWORD   dwMyInfo1;
    VTDWORD   dwMyInfo2;
    .
    .
    .
} MYFILE;
```

Because the `pSpec` passed is essentially the file handle that the view window uses, the developer can redirect the IO on a file-by-file basis while still viewing regular disk-based files.

The `BASEIO` structure is defined as follows:

```
typedef struct BASEIOtag
{
    IOCLOSEPROC pClose;
    IOREADPROC  pRead;
    IOWRITEPROC pWrite;
```

```
IOSEEKPROC pSeek;
IOTELLPROC pTell;
IOGETINFOPROC pGetInfo;
IOOPENPROC pOpen; /* pOpen *MUST* be set to NULL. */
#ifdef NLM
IOSEEK64PROC pSeek64;
IOTELL64PROC pTell64;
#endif
VTVOID *aDummy[3];
} BASEIO, * PBASEIO;
```

The developer must implement the Close, Read, Seek, Tell and GetInfo routines. The Write routine can be a dummy routine and the Open routine must be set to NULL. The first parameter to each of these routines is called hFile and is of the type HIOFILE. HIOFILE is simply the VTLPVOID to your data structure that was passed in the pSpec parameter of the DAOpenDocument call.

The sample source code for a simple implementation of Redirected IO is in the directory samples/taredir. This sample redirects the technology's IO through the fopen, fgetc, fseek, ftell and fclose run-time library routines.

---

**Note:** Redirected IO does not cache the whole file. Seeks can and will occur throughout the file during the course of viewing. If the developer is implementing redirected IO on a slow or sequential link, it is the developer's responsibility to cache the file locally.

---

## 8.2 IOClose

Closes the file identified by hFile and cleans up all memory associated with the file.

### Prototype

```
IOERR IOClose(
    HIOFILE  hFile);
```

### Parameters

- hFile: Identifies the file to be closed. Should be cast into a pointer to your data structure (MYFILE in the preceding discussion).

### Return Values

- IOERR\_OK: Close was successful.
- IOERR\_UNKNOWN: Some error occurred on close.

## 8.3 IORead

Reads data from the current file position forward and resets the position to the byte after the last byte read.

### Prototype

```
IOERR IORead(
    HIOFILE      hFile,
    VTBYTE       * pData,
    VTDWORD      dwSize,
    VTDWORD      * pCount);
```



### Parameters

- **hFile:** Identifies the file to be read. Should be cast into a pointer to your data structure (MYFILE in the preceding discussion).
- **pData:** Points to the buffer into which the bytes should be read. Will be at least **dwSize** bytes big.
- **dwSize:** Number of bytes to read.
- **pCount:** Points to the number of bytes actually read by the function. This value is only valid if the return value is **IOERR\_OK**.

### Return Values

- **IOERR\_OK:** Read was successful. **pCount** contains the number of bytes read and **pData** contains the bytes themselves.
- **IOERR\_EOF:** Read failed because the file pointer was beyond the end of the file at the time of the read.
- **IOERR\_UNKNOWN:** Read failed for some other reason.

## 8.4 IOWrite

Writes data from the current file position forward and resets the position to the byte after the last byte written.

---

**Note:** This function has been fully documented only for completeness. OEMs who use redirected IO do not need to implement writing and the IOWrite function should do nothing but return **IOERR\_UNKNOWN**.

---

### Prototype

```
IOERR IOWrite(
    HIOFILE      hFile,
    VTBYTE       * pData,
    VTDWORD      dwSize,
    VTDWORD      * pCount);
```

### Parameters

- **hFile:** Identifies the file where the data is to be written. Should be cast into a pointer to your data structure (MYFILE in the preceding discussion).
- **pData:** Points to the buffer from which the bytes should be written. It must be at least **dwSize** bytes big.
- **dwSize:** Number of bytes to write.
- **pCount:** Points to the number of bytes actually written by the function. This value is only valid if the return value is **IOERR\_OK**.

### Return Values

- **IOERR\_OK:** Write was successful, **pCount** contains the number of bytes written.
- **IOERR\_UNKNOWN:** Write failed for some reason.

## 8.5 IOSeek

Moves the current file position.

### Prototype

```
IOERR IOSeek(  
    HIOFILE    hFile,  
    VTWORD     wFrom,  
    VTLONG     lOffset);
```

### Parameters

- **hFile:** Identifies the file to be read. Should be cast into a pointer to your data structure (MYFILE in the preceding discussion).
- **wFrom:** One of the following values:
  - **IOSEEK\_TOP:** Move the file position lOffset bytes from the top (beginning) of the file.
  - **IOSEEK\_BOTTOM:** Move the file position lOffset bytes from the bottom (end) of the file.
  - **IOSEEK\_CURRENT:** Move the file position lOffset bytes from the current file position.
- **lOffset:** Number of bytes to move the file pointer. A positive value moves the file pointer forward in the file and a negative value moves it backward. If a requested seek value would move the file pointer before the beginning of the file, the file pointer should remain unchanged and IOERR\_UNKNOWN should be returned. Seeking past EOF is allowed. In that case IOERR\_OK should be returned. IOTell would return the requested seek position and IORead should return IOERR\_EOF and 0 bytes read.

### Return Values

- **IOERR\_OK:** Seek was successful.
- **IOERR\_UNKNOWN:** Seek failed for some reason.

## 8.6 IOTell

Returns the current file position.

### Prototype

```
IOERR IOTell(  
    HIOFILE    hFile,  
    VTDWORD    * pOffset);
```

### Parameters

- **hFile:** Identifies the file to be read. Should be cast into a pointer to your data structure (MYFILE in the preceding discussion).
- **pOffset:** Points to the current file position returned by the function.

### Return Values

- **IOERR\_OK:** Tell was successful.
- **IOERR\_UNKNOWN:** Tell failed for some reason.

## 8.7 IOGetInfo

Returns information about an open file.

### Prototype

```
IOERR IOGetInfo(
    HIOFILE      hFile,
    VTDWORD      dwInfoId,
    VTVOID       * pInfo);
```

### Parameters

- **hFile**: Identifies the file to be read. Should be cast into a pointer to your data structure (MYFILE in the previous discussion).
- **dwInfoId**: One of the following values:
  - **IOGETINFO\_FILENAME**: pInfo points to a string that should be filled with the base file name (no path) of the open file (for example TEST.DOC). If you do not know the file name, return IOERR\_UNKNOWN. Certain file types (such as DataEase) must know the original file name in order to open secondary files required to correctly view the original file. If you return IOERR\_UNKNOWN, these file types will not convert. See the description of IOGETINFO\_GENSECONDARY in [Section 8.7.1, "IOGENSECONDARY and IOGENSECONDARYW Structures."](#)
  - **IOGETINFO\_PATHNAME**: pInfo points to a string that should be filled with the fully qualified path name (including the file name) of the open file. For example, C:\MYDIR\TEST.DOC. If you do not know the path name, return IOERR\_UNKNOWN.
  - **IOGETINFO\_PATHTYPE**: pInfo points to a DWORD that should be filled with the IOTYPE of the path returned by IOGETINFO\_PATHNAME. For instance, if you return a DOS path name in the Unicode character set, you should return IOTYPE\_UNICODEPATH.
  - **IOGETINFO\_ISOLE2STORAGE**: Must return IOERR\_FALSE. pInfo is not used.
  - **IOGETINFO\_GENSECONDARY**: pInfo points to a structure of type IOGENSECONDARY. Some file types require supporting files to be opened. These supporting files may contain formatting information or extra data. Correct handling of IOGETINFO\_GENSECONDARY is critical to the operation of the Outside In technology. For a list of these file types, see [Section 8.7.2, "File Types That Cause IOGETINFO\\_GENSECONDARY."](#)

Because the developer is in total control of the IO for the primary file, the technology does not know how to generate a path to these secondary files or even if the secondary files are accessible through the regular file system. The IOGETINFO\_GENSECONDARY call gives the developer a chance to resolve this problem by generating a new IO specification for the secondary file in question. The developer gets just the base file name (often embedded in the original document or generated from the primary file's name) of the secondary file.

The developer may either use one of the standard Outside In IO types or totally redirect the IO for the secondary file, as well. For more details, see [Section 8.7.1, "IOGENSECONDARY and IOGENSECONDARYW Structures."](#)

- IOGETINFO\_64BITIO: For redirected I/O that wishes to use 64-bit seek/tell functions, your IOGetInfo function must respond IOERR\_TRUE to this dwInfoId. In addition, the pSeek64/pTell64 items in the baseio structure must be valid pointers to the proper function types.

Any other value should return IOERR\_BADINFOID.

- pInfo: The size of the pInfo buffer depends on the dwInfoId selected. For IOGETINFO\_FILENAME and IOGETINFO\_PATHNAME, the buffer is of size MAX\_PATH characters (each character is either one byte or two, depending on PATHTYPE). The IOGETINFO\_PATHTYPE buffer is the size of a VTDWORD.

### Return Values

- IOERR\_OK: GetInfo was successful.
- IOERR\_TRUE: Affirmative response from a true or false GetInfo.
- IOERR\_FALSE: Negative response from a true or false GetInfo.
- IOERR\_BADINFOID: dwInfoId can not be handled by this file type.
- IOERR\_INVALIDSPEC: The file spec is bad for this type.
- IOERR\_UNKNOWN: GetInfo failed for some other reason.

## 8.7.1 IOGENSECONDARY and IOGENSECONDARYW Structures

These structures are passed to the developer through the IOGetInfo function. They allow the developer to tell the technology where a secondary file, needed to view the primary file, is located.

The SpecType of the original file determines which of these two structures is used. If the SpecType is IOTYPE\_UNICODEPATH, IOGENSECONDARYW is used. pFileName will point to a Unicode string terminated with a NULL WORD. For all other SpecTypes, IOGENSECONDARY is used and pFileName will point to a string terminated with a NULL BYTE.

The following is a C data structure defined in SCCIO.H:

```
typedef struct
{
    VTDWORD      dwSize;
    VTLPBYTE     pFileName;
    VTDWORD      dwSpecType;
    VTLPVOID     pSpec;
    VTDWORD      dwOpenFlags
} IOGENSECONDARY, * PIOGENSECONDARY;

typedef struct
{
    VTDWORD      dwSize;
    VTLPWORD     pFileName;
    VTDWORD      dwSpecType;
    VTLPVOID     pSpec;
    VTDWORD      dwOpenFlags
} IOGENSECONDARYW, * PIOGENSECONDARYW;
```

- dwSize: Will be set to sizeof (IOGENSECONDARY) or sizeof (IOGENSECONDARYW) (both of these values are the same).
- pFileName: A pointer to a string representing the file name of the secondary file that the technology requires. It will generally be a name that is stored in the

primary file somewhere (such as MYSTYLE.STY for a Word for DOS file) or a name generated from the primary file name (the primary file for a DataEase database will always have a .dba extension, the secondary name would be the same file name but with a .dbm extension).

- dwSpecType: The developer must fill this with the IOSPEC for the secondary file.
- pSpec: On entry, this pointer points to an array of 1024 bytes. If the dwSpecType is set a regular IOTYPE such as IOTYPE\_ANSIPATH, the developer may fill this array with the path name or structure required for that IOTYPE. If the developer is redirecting access to the secondary file, then dwSpecType will be IOTYPE\_REDIRECT and the developer should replace pSpec with a pointer to a developer-defined structure that begins with the BASEIO structure (see [Section 8.1, "Using Redirected IO"](#)).

Note the file is supposed to be opened by the OEM's redirected IO code by the time they return the BASEIO struct. This is because the pOpen routine in the BASEIO struct is supposed to be NULL.

- dwOpenFlags: Set by the technology. A set of bit flags describing how the secondary file should be opened. Multiple flags may be used by bitwise OR-ing them together. The following flags are currently used:
  - IOOPEN\_READ: The secondary file should be opened for read.
  - IOOPEN\_WRITE: The secondary file should be opened for write. Please note that if the specified file already exists, it's contents will be erased when this flag is set.
  - IOOPEN\_CREATE: The secondary file should be created (if it does not already exist) and opened for write.

## 8.7.2 File Types That Cause IOGETINFO\_GENSECONDARY

The following details concern specific file types.

- Microsoft Word for DOS Versions 4, 5 and 6: Used to open and read the style sheet file associated with the document. The filter will successfully degrade if the style sheet is not present.
- Harvard Graphics DOS 3.x: Used to open and read the individual slides within ScreenShow and palette files. Files with the extension .ch3 are individual graphics or slides that can be opened using no secondary files. Files with the extension .sy3 are ScreenShows that reference a list of .ch3 files via the secondary file mechanism. There is also an optional palette file that can be referenced from a .ch3 file, but the filter will successfully degrade if the palette file is not present.
- R:Base: Used to open and read required schema file. The R:Base data files are named xxxx2.rbf but the data is useless without the schema file named xxxx1.rbf. There is also a xxxx3.rbf file associated with each database, but it is not used.
- Paradox 4.0 and Above: Used to open and read memo field data file. Paradox uses a separate file for all memo field data larger than 32 bytes.
- DataEase: Used to open and read the data file. DataEase databases include a .dba file that contains the schema (the file that the technology can identify as DataEase) and a .dbm file that contains the actual data.

## 8.8 IOSEEK64PROC / IOTELL64PROC

These functions are for seek/tell using 64-bit offsets. These functions are not used by default. Rather, they are used if the IOGETINFO\_64BITIO message returns IOERR\_TRUE. This is so redirected I/O using strictly 32-bit I/O is unaffected.

### 8.8.1 IOSeek64

Moves the current file position.

#### Prototype

```
IOERR IOSeek64(  
HIOFILE hFile,  
VTWORD wFrom,  
VTOFF_T offset);
```

#### Parameters

The parameter information is the same as for IOSeek(). However, the size of the VTOFF\_T offset for IOSeek64() is 64-bit unlike the 32-bit offset in IOSeek().

### 8.8.2 IOTell64

Returns the current file position.

#### Prototype

```
IOERR IOTell64(  
HIOFILE hFile,  
VTOFF_T * pOffset);
```

#### Parameters

The parameter information is the same as for IOTell(). The only change is the use of a pointer to a 64-bit parameter for returning the offset.

---

## Implementation Issues

This chapter discusses potential issues in using Content Access.

### 9.1 Running in 24x7 Environments

To ensure robust 24x7 performance in server applications embedding this product, it is strongly recommended that the technology be run in a process separate from the server's primary process.

The file filtering technology underlying the software represents almost a quarter of a million lines of code. This code is expected to robustly deal with any stream of bytes, of any length (any file), in all cases. Oracle has dedicated, and continues to dedicate, significant effort into making this technology extremely robust. However, in real world situations, expect that some small number of malformed files may force the filters into unstable states. This generally results in either a memory exception (which can be trapped and recovered from gracefully), infinite loop or a wild pointer that causes the filter to write into memory that is part of the same process but does not belong to the filter. In the latter situation, this wild pointer condition cannot be trapped.

On the desktop this is not a significant problem since the number of files being dealt with is relatively small. In a 24x7 server environment, however, a wild pointer can be extremely disruptive to the server process and produce serious problems. The best solution for dealing with this problem is to run any application that reads complex file formats, including Content Access, in a separate process. This solution protects the application from the susceptibility of filtering technology to the unknown quality of input files.

It must be stressed that files that lead to wild pointers or infinite loops occur very infrequently, usually as a result of a third-party conversion process or beta versions of applications. Oracle is committed to addressing these issues and to updating and expanding its testing tools and corpus of documents to proactively minimize this garbage in-garbage out problem.





---

## Sample Applications

Each of the sample applications included in this SDK is designed to highlight a specific aspect of the technology's functionality. We ship built versions of these sample applications. The compiled executables should be in the root directory where the product is installed.

The following copyright applies to all sample applications shipped with this product:

**Copyright © Oracle 1993, 2011**

**All rights reserved.**

**You have a royalty-free right to use, modify, reproduce and distribute the Sample Applications (and/or any modified version) in any way you find useful, provided that you agree that Oracle has no warranty obligations or liability for any Sample Application files.**

### 10.1 Building the Samples on a Windows System

Microsoft Visual Studio project files are provided for building each of the sample applications. For 32-bit versions of Windows, versions of the project files are provided for Visual Studio 6 (.dsp files) and Visual Studio 2005 (.vcproj files).

---

**Note:** Because .vcproj files may not pick up the right compiler on their own, you need to make sure that you are building with the Win64 configuration in Visual Studio 2005. For 64-bit versions of Windows, only the Visual Studio 2005 versions are available.

---

The project files for the sample applications can be found in the \sdk\samplecode\win subdirectory of the Outside In SDK.

### 10.2 Building the Samples on a UNIX System

See the following sections for specific information about building the sample applications on your flavor of UNIX:

- [Section 3.8, "HP-UX Compiling and Linking"](#)
- [Section 3.9, "IBM AIX Compiling and Linking"](#)
- [Section 3.10, "Linux Compiling and Linking"](#)
- [Section 3.11, "Oracle Solaris Compiling and Linking"](#)
- [Section 3.12, "FreeBSD Compiling and Linking"](#)

## 10.3 An Overview of the Sample Applications

Here's a quick tour of the sample applications provided with this product.

---

---

**Note:** Please note that not all of the sample applications are provided for both the Windows and UNIX platforms. See the heading of each application's subsection for clarification.

---

---

### 10.3.1 casample

An example of a typical usage of the Outside In Content Access API is casample. Because this is intended as a simple template or reference for common Content Access usage, it creates only rudimentary output. However, it does initialize, exercise and cleanup Content Access output. Content Access requires the usage of the Outside In Data Access module. Therefore, this application also demonstrates usage of a portion of Data Access.

The application is executed from the command line and takes only one parameter, the name of the input file:


```
casample input_file
```

### 10.3.2 tademo (Windows Only)

The tademo sample application included with this product provides a simple demonstration of text access. The text from a file is read a block at a time and displayed in the tademo window. The TAREadFirst and TAREadNext functions are directly tied to menu options, and the block size may be set by the user. An option is also provided to save the text to a file.

This tutorial is specific to the Windows application tademo, though the UNIX application textdemo is almost identical. The following sections assume the reader has a basic understanding of the structure of Windows executable source code and Windows API calls.

Figure 10-1 OIT Text Access Demo



### 10.3.2.1 Overview

The bulk of this sample application is in six functions, as detailed in the following sections.

### 10.3.2.2 MainWndProc

```

LRESULT MainWndProc (
    HWND    hwnd,
    UINT     message,
    WPARAM   wParam,
    LPARAM   lParam )

```

This is the window procedure for the main program window. It is responsible for processing menu options. It includes an information bar at the top that displays the name of the open file, the block read size, and the number and size of the currently displayed block.

### 10.3.2.3 DisplayWndProc

```

long FAR PASCAL DisplayWndProc (
    HWND    hwnd,
    UINT     message,
    WPARAM   wParam,
    LPARAM   lParam )

```

This is the window procedure for the window that displays the document text.

### 10.3.2.4 DoTextOpen

```

int DoTextOpen (
    HWND    hwnd )

```

This function is called when the user selects the **File** menu, then the chooses **Open**. It calls `DAOpenDocument` then `TAOpenText` to initiate text access for the file.

### 10.3.2.5 DoTextClose

```
VTVOID DoTextClose()
```

This function simply closes the text and data access handles generated by DoTextOpen, then frees the buffer used by the TReadFirst and TReadNext functions.

### 10.3.2.6 DoSaveTextAs

```
VTVOID DoSaveTextAs(  
    HWND      hwnd)
```

DoSaveTextAs writes the document's text to a file. In this sample application, the text is always written to the file C:\tademo.txt, but the methods used in the DoSaveTextAs function could easily be enhanced for more flexible options.

### 10.3.2.7 DoTextBlockAccess

```
DAERR DoTextBlockAccess(  
    HWND      hwnd,  
    WORD      wType )
```

This function is called whenever the user chooses the **First Block** or **Next Block** menu items. It calls text access to retrieve a block of text from the file, then makes the block available for display in the program window.

## 10.3.3 taredir (UNIX Only)

This sample provides a means of using the API presented in this guide without the need for Motif libraries. All extracted text is output to the standard output device, or can be redirected to a file or another device.

## 10.3.4 textdemo (UNIX Only)

The sample code in the textdemo files shows how to use the API presented in this guide. This application is essentially identical to the Windows-only application tademo, which is discussed at length in [Section 10.3.2, "tademo \(Windows Only\)."](#)

---

# Copyrights and Licensing

This appendix provides a comprehensive overview of all copyright and licensing information for Outside In Content Access.

## A.1 Outside In Content Access Licensing

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Portions relating to XServer copyright 1990, 1991 Network Computing Devices, 1987 Digital Equipment Corporation and the Massachusetts Institute of Technology.

Portions relating to PNG copyright 1999, 2000, 2001, 2002 Greg Roelofs.

Portions relating to PNG Copyright 1995-1996 Jean-loup Gailly and Mark Adler

Portions relating to PNG Copyright 1998, 1999 Glenn Randers-Pehrson, Tom Lane, Willem van Schaik, John Bowler, Kevin Bracey, Sam Bushell, Magnus Holmgren, Greg Roelofs, Tom Tanner, Andreas Dilger, Dave Martindale, Guy Eric Schalnat, Paul Schmidt, Tim Wegner

Portions relating to JPEG and to color quantization copyright 2000, 2001, 2002, Doug Becker and copyright (C) 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, Thomas G. Lane. This software is based in part on the work of the Independent JPEG Group. See the file README-JPEG.TXT for more information.

Portions relating to WBMP copyright 2000, 2001, 2002 Maurice Szmurlo and Johan Van den Brande.

Portions relating to GIF Copyright 1987, by Steven A. Bennett.

UnRAR - free utility for RAR archives

License for use and distribution of FREE portable version

The source code of UnRAR utility is freeware. This means:

1. All copyrights to RAR and the utility UnRAR are exclusively owned by the author - Alexander Roshal.
2. The UnRAR sources may be used in any software to handle RAR archives without limitations free of charge, but cannot be used to re-create the RAR compression algorithm, which is proprietary. Distribution of modified UnRAR sources in separate form or as a part of other software is permitted, provided that it is clearly stated in the documentation and source comments that the code may not be used to develop a RAR (WinRAR) compatible archiver.
3. The UnRAR utility may be freely distributed. No person or company may charge a fee for the distribution of UnRAR without written permission from the copyright holder.
4. THE RAR ARCHIVER AND THE UNRAR UTILITY ARE DISTRIBUTED "AS IS". NO WARRANTY OF ANY KIND IS EXPRESSED OR IMPLIED. YOU USE AT YOUR OWN RISK. THE AUTHOR WILL NOT BE LIABLE FOR DATA LOSS, DAMAGES, LOSS OF PROFITS OR ANY OTHER KIND OF LOSS WHILE USING OR MISUSING THIS SOFTWARE.
5. Installing and using the UnRAR utility signifies acceptance of these terms and conditions of the license.

6. If you don't agree with terms of the license you must remove UnRAR files from your storage devices and cease to use the utility.

JasPer License Version 2.0

Copyright (c) 2001-2006 Michael David Adams

Copyright (c) 1999-2000 Image Power, Inc.

Copyright (c) 1999-2000 The University of British Columbia

All rights reserved.

Permission is hereby granted, free of charge, to any person (the "User") obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

1. The above copyright notices and this permission notice (which includes the disclaimer below) shall be included in all copies or substantial portions of the Software.
2. The name of a copyright holder shall not be used to endorse or promote products derived from the Software without specific prior written permission.

THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF THE SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER. THE SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. NO ASSURANCES ARE PROVIDED BY THE COPYRIGHT HOLDERS THAT THE SOFTWARE DOES NOT INFRINGE THE PATENT OR OTHER INTELLECTUAL PROPERTY RIGHTS OF ANY OTHER ENTITY. EACH COPYRIGHT HOLDER DISCLAIMS ANY LIABILITY TO THE USER FOR CLAIMS BROUGHT BY ANY OTHER ENTITY BASED ON INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OR OTHERWISE. AS A CONDITION TO EXERCISING THE RIGHTS GRANTED HEREUNDER, EACH USER HEREBY ASSUMES SOLE RESPONSIBILITY TO SECURE ANY OTHER INTELLECTUAL PROPERTY RIGHTS NEEDED, IF ANY. THE SOFTWARE IS NOT FAULT-TOLERANT AND IS NOT INTENDED FOR USE IN MISSION-CRITICAL SYSTEMS, SUCH AS THOSE USED IN THE OPERATION OF NUCLEAR FACILITIES, AIRCRAFT NAVIGATION OR COMMUNICATION SYSTEMS, AIR TRAFFIC CONTROL SYSTEMS, DIRECT LIFE SUPPORT MACHINES, OR WEAPONS SYSTEMS, IN WHICH THE FAILURE OF THE SOFTWARE OR SYSTEM COULD LEAD DIRECTLY TO DEATH, PERSONAL INJURY, OR SEVERE PHYSICAL OR ENVIRONMENTAL DAMAGE ("HIGH RISK ACTIVITIES"). THE COPYRIGHT HOLDERS SPECIFICALLY DISCLAIM ANY EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR HIGH RISK ACTIVITIES.





---

## Content Access Options

Options are parameters affecting the behavior of the Outside In Technology. These options are available to the developer when using Content Access. They are set using the `DASetOption` call. It is recommended that developers familiarize themselves with all of the options available.

Options may be Local, in which case they only affect the handle for which they are set, or Global, in which case they automatically affect all handles associated with the `hDoc`.

While default values are provided, users are encouraged to set all options for a number of reasons. In some cases, the default values were chosen to provide backwards compatibility. In other cases, the default values were chosen arbitrarily from a range of possibilities.

### B.1 Character Mapping

This section discusses character mapping.

#### B.1.1 `SCCOPT_DEFAULTINPUTCHARSET`

This option is used in cases where Outside In cannot determine the character set used to encode the text of an input file. When all other means of determining the file's character set are exhausted, Outside In will assume that an input document is encoded in the character set specified by this option. This is most often used when reading plain-text files, but may also be used when reading HTML or PDF files. The possible character sets are listed in `charsets.h`.

When "extended test for text" is enabled (see [Section B.2.3, "SCCOPT\\_FIFLAGS"](#)), this option will still apply to plain-text input files that are not identified as EBCDIC or Unicode.

This option supersedes the `SCCOPT_FALLBACKFORMAT` option for selecting the character set assumed for plain-text files. For backwards compatibility, use of deprecated character-set -related values is still currently supported for `SCCOPT_FALLBACKFORMAT`, though internally such values will be translated into equivalent values for the `SCCOPT_DEFAULTINPUTCHARSET`. As a result, if an application were to set both options, the last such value set for either option will be the value that takes effect.

#### Handle Types

`NULL`, `VTHDOC`

#### Scope

Global

**Data Type**

VTDWORD

**Default**

- ANSI1252 on Windows and Latin-1 on UNIX

**Data**

The data types are listed in charsets.h.

**B.1.2 SCCOPT\_OUTPUTCHARACTERSET**

Any text returned by Content Access or Text Access will be in the specified character set.

**Handle Types**

VTHDOC, VTHCONTENT, VTHTEXT

**Scope**

Local

**Data Type**

VTDWORD

**Default**

If the option is not set, Content Access will use SO\_ANSI1252 on all non-Windows platforms. The current ANSI code page will be retrieved on Windows using GetACP() with the result being mapped to match an Outside In Technology character set.

**Data**

One of the following values:

Value	Description
CS_DOS_437	U.S.
CS_DOS_737	Greek
CS_DOS_850	Latin-1
CS_DOS_852	Latin-2
CS_DOS_855	Cyrillic
CS_DOS_857	Turkish
CS_DOS_860	Portuguese
CS_DOS_863	French Canada
CS_DOS_865	Denmark, Norway-DAT
CS_DOS_866	Cyrillic
CS_DOS_869	Greece
CS_WINDOWS_874	Thailand
CS_WINDOWS_932	Japanese
CS_WINDOWS_936	Chinese GB

Value	Description
CS_WINDOWS_949	Korea (Wansung)
CS_WINDOWS_950	Hong Kong, Taiwan
CS_WINDOWS_1250	Windows Latin 2 (Central Europe)
CS_WINDOWS_1251	Windows Cyrillic (Slavic)
CS_WINDOWS_1252	Windows Latin 1 (ANSI)
CS_WINDOWS_1253	Windows Greek
CS_WINDOWS_1254	Windows Latin 5 (Turkish)
CS_WINDOWS_1255	Windows Hebrew
CS_WINDOWS_1256	Windows Arabic
CS_WINDOWS_1257	Windows Baltic
CS_UNICODE	Unicode
CS_ISO8859_1	Latin-1 - this is a subset of Windows 1252
CS_ISO8859_2	Latin-2
CS_ISO8859_3	Latin-3
CS_ISO8859_4	Latin-4
CS_ISO8859_5	Cyrillic
CS_ISO8859_6	Arabic
CS_ISO8859_7	Greek
CS_ISO8859_8	Hebrew
CS_ISO8859_9	Turkish

### B.1.3 SCCOPT\_UNMAPPABLECHAR

This option selects the character used when a character cannot be found in the output character set. This option takes the Unicode value for the replacement character. It is left to the user to make sure that the selected replacement character is available in the output character set.

#### Handle Types

VTHDOC

#### Scope

Local

#### Data Type

VTWORD

#### Data

The Unicode value for the character to use.

#### Default

- 0x002a = "\*"

## B.2 Input Handling

This section discusses input handling.

### B.2.1 SCCOPT\_EXTRACTXMPMETADATA

Adobe's Extensible Metadata Platform (XMP) is a labeling technology that allows you to embed data about a file, known as metadata, into the file itself. This option enables the XMP feature, which does not interpret the XMP metadata, but passes it straight through without any interpretation. This option is independent of the other two "metadata" options. This option will be ignored if the SCCOPT\_PARSEXMPMETADATA option is enabled.

- SCCEX\_IND\_SUPPRESSPROPERTIES will not affect XMP, so if you turn XMP on, but also set SuppressProperties, you will still get the XMP.
- SCCEX\_METADATAONLY will not guarantee that XMP is produced.

#### Handle Types

VTHDOC

#### Scope

Local (was Global prior to release 8.2.2)

#### Data Type

VTBOOL

#### Data

- TRUE: This setting enables XMP extraction.
- FALSE: This setting disables XMP extraction.

#### Default

- FALSE

### B.2.2 SCCOPT\_FALLBACKFORMAT

This option controls how files are handled when their specific application type cannot be determined. This normally affects all plain-text files, because plain-text files are generally identified by process of elimination, for example, when a file isn't identified as having been created by a known application, it is treated as a plain-text file.

A number of values that were formerly allowed for this option have been deprecated. Specifically, the values that selected specific plain-text character sets are no longer to be used. For such functionality, applications should instead use the option [Section B.1.1, "SCCOPT\\_DEFAULTINPUTCHARSET."](#)

#### Handle Types

NULL, VTHDOC

#### Scope

Global

**Data Type**

VTDWORD

**Data**

The high VTWORD of this value is reserved and should be set to 0, and the low VTWORD must have one of the following values:

- FI\_TEXT: Unidentified file types will be treated as text files.
- FI\_NONE: Outside In will not attempt to process files whose type cannot be identified. This will include text files. When this option is selected, an attempt to process a file of unidentified type will cause Outside In to return an error value of DAERR\_FILTERNOTAVAIL (or SCCERR\_NOFILTER).

**Default**

- FI\_TEXT

**B.2.3 SCCOPT\_FIFLAGS**

This option affects how an input file's internal format (application type) is identified when the file is first opened by the Outside In technology. When the extended test flag is in effect, and an input file is identified as being either 7-bit ASCII, EBCDIC, or Unicode, the file's contents will be interpreted as such by the viewing process.

The extended test is optional because it requires extra processing and cannot guarantee complete accuracy (which would require the inspection of every single byte in a file to eliminate false positives.)

**Handle Types**

NULL, VTHDOC

**Scope**

Global

**Data Type**

VTDWORD

**Data**

One of the following values:

- SCCUT\_FI\_NORMAL: This is the default value. When this is set, standard file identification behavior occurs.
- SCCUT\_FI\_EXTENDEDTEST: If set, the File Identification code will run an extended test on all files that are not identified.

**Default**

- SCCUT\_FI\_NORMAL

**B.2.4 SCCOPT\_IGNORE\_PASSWORD**

This option can disable the password verification of files where the contents can be processed without validation of the password. If this option is not set, the filter should prompt for a password if it handles password-protected files.

As of Release 8.3.5, only the PST Filter supports this option.

**Scope**

Global

**Data Type**

VTBOOL

**Data**

- TRUE: Ignore validation of the password
- FALSE: Prompt for the password

**Default**

FALSE

## B.2.5 SCCOPT\_LOTUSNOTESDIRECTORY

This option allows the developer to specify the location of a Lotus Notes or Domino installation for use by the NSF filter. A valid Lotus installation directory must contain the file nnotes.dll.

---

---

**Note:** Please see section 2.1.1 for NSF support on Win32 or section 3.1.1 for NSF support on Linux x86-32 or Solaris Sparc 32.

---

---

**Handle Types**

NULL

**Scope**

Global

**Data Type**

VTLPBYTE

**Data**

A path to the Lotus Notes directory.

**Default**

If this option isn't set, then OIT will first attempt to load the Lotus library according to the operating system's PATH environment variable, and then attempt to find and load the Lotus library as indicated in HKEY\_CLASSES\_ROOT\Notes.Link.

## B.2.6 SCCOPT\_PARSEXMPMETADATA

Adobe's Extensible Metadata Platform (XMP) is a labeling technology that allows you to embed data about a file, known as metadata, into the file itself. This option enables parsing of the XMP data into normal OIT document properties. Enabling this option may cause the loss of some regular data in premium graphics filters (such as Postscript), but won't affect most formats (such as PDF).

**Handle Types**

VTHDOC

**Scope**

Local

**Data Type**

VTBOOL

**Data**

- TRUE: This setting enables parsing XMP.
- FALSE: This setting disables parsing XMP.

**Default**

FALSE

**B.2.7 SCCOPT\_PDF\_FILTER\_REORDER\_BIDI**

This option controls whether or not the PDF filter will attempt to reorder bidirectional text runs so that the output is in standard logical order as used by the Unicode 2.0 and later specification. This additional processing will result in slower filter performance according to the amount of bidirectional data in the file.

**Handle Types**

VTHDOC, NULL

**Scope**

Global

**Data Type**

VTDWORD

**Data**

- SCCUT\_FILTER\_STANDARD\_BIDI
- SCCUT\_FILTER\_REORDERED\_BIDI

**Default**

SCCUT\_FILTER\_STANDARD\_BIDI

**B.2.8 SCCOPT\_PROCESS\_OLE\_EMBEDDINGS**

Microsoft Powerpoint versions from 1997 through 2003 had the capability to embed OLE documents in the Powerpoint files. This option controls which embeddings are to be processed as native (OLE) documents and which are processed using the alternate graphic.

---

---

**Note:** The Microsoft Powerpoint application sometimes does embed known Microsoft OLE embeddings (such as Visio, Project) as an "Unknown" type. To process these embeddings, the SCCOPT\_PROCESS\_OLEEMBED\_ALL option is required. Post Office-2003 products such as Office 2007 embeddings also fall into this category.

---

---

**Handle Types**

VTHDOC, NULL

**Scope**

Global

**Data Type**

VTWORD

**Data**

- SCCOPT\_PROCESS\_OLEEMBED\_ALL : Process all embeddings in the file
- SCCOPT\_PROCESS\_OLEEMBED\_NONE : Process none of the embeddings in the file
- SCCOPT\_PROCESS\_OLEEMBED\_STANDARD (default) : Process embeddings that are known standard embeddings. These include Office 2003 versions of Word, Excel, Visio etc.

**Default**

SCCOPT\_PROCESS\_OLEEMBED\_STANDARD

**B.2.9 SCCOPT\_TIMEZONE**

This option allows the user to define an offset to GMT that will be applied during date formatting, allowing date values to be displayed in a selectable time zone. This option affects the formatting of numbers that have been defined as date values (for example, most dates in spreadsheet cells). This option will not affect dates that are stored as text.

**Handle Types**

NULL, VTHDOC

**Scope**

Global

**Data Type**

VTLONG

**Data**

Integer parameter from -96 to 96, representing 15-minute offsets from GMT. To query the operating system for the time zone set on the machine, specify SCC\_TIMEZONE\_USENATIVE.

**Default**

- 0: GMT time



## B.3 Compression

This section discusses compression.

### B.3.1 SCCOPT\_FILTERJPG

This option can disable access to any files using JPEG compression, such as JPG graphic files or TIFF files using JPEG compression, or files with embedded JPEG graphics. Attempts to read or write such files when this option is enabled will fail and return the error `SCCERR_UNSUPPORTEDCOMPRESSION` if the entire file is JPEG compressed, and grey boxes for embedded JPEG-compressed graphics.

The following is a list of file types affected when this option is disabled:

- JPG files
- Postscript files containing JPG images
- PDFs containing JPEG images

Note that the setting for this option overrides the requested output graphic format when there is a conflict.

#### Handle Types

HDOC, HEXPORT

#### Scope

Local

#### Data Type

VTDWORD

#### Data

- `SCCVW_FILTER_JPG_ENABLED`: Allow access to files that use JPEG compression
- `SCCVW_FILTER_JPG_DISABLED`: Do not allow access to files that use JPEG compression

#### Default

`SCCVW_FILTER_JPG_ENABLED`

### B.3.2 SCCOPT\_FILTERLZW

This option can disable access to any files using Lempel-Ziv-Welch (LZW) compression, such as .GIF files, .ZIP files or self-extracting archive (.EXE) files containing "shrunk" files. Attempts to read such files when this option is enabled will fail and return the error `SCCERR_UNSUPPORTEDCOMPRESSION`. Unlike many other options, this option must be set programmatically, as it is not stored or read on startup.

The following is a list of file types affected when this option is disabled:

- GIF files
- TIF files using LZW compression
- PDF files that use internal LZW compression

- TAZ and TAR archives containing files that are identified as FI\_UNIXCOMP
- ZIP and self-extracting archive (.EXE) files containing "shrunk" files
- Postscript files using LZW compression

Although this option can disable access to files in ZIP or EXE archives stored using LZW compression, any files in such archives that were stored using any other form of compression will still be accessible.

**Handle Types**

HDOC

**Scope**

Local

**Data**

- SCCVW\_FILTER\_LZW\_ENABLED: LZW compressed files will be read normally.
- SCCVW\_FILTER\_LZW\_DISABLED: LZW compressed files will not be read.

**Default**

SCCVW\_FILTER\_LZW\_ENABLED

## B.4 Content Access Flags

The following section discusses content access flags.

### B.4.1 SCCOPT\_ENABLEALLSUBOBJECTS

Outside In has an internal flag that is used to optimize several of the input filters for searching. One of the side effects of this optimization is that many embedded bitmaps, including Progressive JPEG, aren't output by the filter. SCCOPT\_ENABLEALLSUBOBJECTS can override this internal optimization.

**Handle Types**

VTHDOC

**Scope**

Local

**Data Type**

VTDWORD

**Data**

One of the following values:

- SCCVW\_FILTER\_ENABLEALLSUBOBJECTS: Override the optimizations.
- SCCVW\_FILTER\_NORMALSUBOBJECTS: Allow the optimizations.

**Default**

SCCVW\_FILTER\_NORMALSUBOBJECTS

## B.4.2 SCCOPT\_CA\_FLAGS

This option allows the developer to set a flag to enable an option unique to Content Access.

### Handle Types

VTHDOC

### Scope

Local

### Data Type

DWORD

### Data

- **SCCEX\_IND\_GENERATED**: Includes data not originally stored as text in the input document. This can be important content the user would see when viewing the document in the original application (time and owner information in archives, numbers in spreadsheets/databases, and so forth).
- **SCCEX\_IND\_GENERATESYSTEMMETADATA**: When this flag is set, system metadata will be generated. This text is "generated," so it will be affected by **SCCEX\_IND\_GENERATED**. This information is gathered through system calls and may adversely affect performance.

### Default

- 0: The flag is turned off.

## B.4.3 SCCOPT\_FORMATFLAGS

This option allows the developer to set flags that enable options that span multiple export products.

### Handle Types

VTHDOC

### Scope

Local

### Data Type

VTDWORD

### Data

- **SCCOPT\_FLAGS\_ALLISODATETIMES**: When this flag is set, all Date and Time values are converted to the ISO 8601 standard. This conversion can only be performed using dates that are stored as numeric data within the original file.
- **SCCOPT\_FLAGS\_STRICTFILEACCESS**: When an embedded file or URL can't be opened with the full path, OIT will sometimes try and open the referenced file from other locations, including the current directory. When this flag is set, it will prevent OIT from trying to open the file from any location other than the fully qualified path or URL.

**Default**

0: All flags turned off

## B.5 File System

This section discusses file systems.

### B.5.1 SCCOPT\_IO\_BUFFERSIZE

This provides three options that allow the user to adjust buffer sizes to take advantage of faster computers/more memory. This is an advanced option that casual users of Content Access may ignore. This option allows the users to tune Content Access memory usage to a particular target machine. The number specified will be in kilobytes.

**Handle Type**

NULL, VTHDOC

**Scope**

Global

**Data Type**

SCCBUFFEROPTIONS Structure

**Data**

A buffer options structure

#### B.5.1.1 SCCBUFFEROPTIONS Structure

```
typedef struct SCCBUFFEROPTIONStag
{
    VTDWORD dwReadBufferSize;    /* size of the I/O Read buffer
                                  in KB */
    VTDWORD dwMMapBufferSize;    /* maximum size for the I/O
                                  Memory Map buffer in KB */
    VTDWORD dwTempBufferSize;    /* maximum size for the memory-
                                  mapped temp files in KB */
    VTDWORD dwFlags;             /* use flags */
} SCCBUFFEROPTIONS, *PSCCBUFFEROPTIONS;
```

**Parameters**

- **dwReadBufferSize:** Used to define the number of bytes that will read from disk into memory at any given time. Once the buffer has data, further file reads will proceed within the buffer until the end of the buffer is reached, at which point the buffer will again be filled from the disk. This can lead to performance improvements in many file formats, regardless of the size of the document.
- **dwMMapBufferSize:** Used to define a maximum size that a document can be and use a memory-mapped I/O model. In this situation, the entire file is read from disk into memory and all further I/O is performed on the data in memory. This can lead to significantly improved performance, but note that either the entire file can be read into memory, or it cannot. If both of these buffers are set, then if the file is smaller than the dwMMapBufferSize, the entire file will be read into memory; if not, it will be read in blocks defined by the dwReadBufferSize.

- `dwTempBufferSize`: The maximum size that a temporary file can occupy in memory before being written to disk as a physical file. Storing temporary files in memory can boost performance on archives, files that have embedded objects or attachments. If set to 0, all temporary files will be written to disk.
- `dwFlags`
  - `SCCBUFOPT_SET_READBUFSIZE 1`
  - `SCCBUFOPT_SET_MMAPBUFSIZE 2`
  - `SCCBUFOPT_SET_TEMPBUFSIZE 4`

To set any of the three buffer sizes, set the corresponding flag while calling `dwSetOption`.

### Default

The default settings for these options are:

- `#define SCCBUFOPT_DEFAULT_READBUFSIZE 2`: A 2KB read buffer.
- `#define SCCBUFOPT_DEFAULT_MMAPBUFSIZE 8192`: An 8MB memory-map size.
- `#define SCCBUFOPT_DEFAULT_TEMPBUFSIZE 2048`: A 2MB temp-file limit.

Minimum and maximum sizes for each are:

- `SCCBUFOPT_MIN_READBUFSIZE 1`: Read one Kbyte at a time.
- `SCCBUFOPT_MIN_MMAPBUFSIZE 0`: Don't use memory-mapped input.
- `SCCBUFOPT_MIN_TEMPBUFSIZE 0`: Don't use memory temp files
- `SCCBUFOPT_MAX_READBUFSIZE 0x003fffff`, `SCCBUFOPT_MAX_MMAPBUFSIZE 0x003fffff`, `SCCBUFOPT_MAX_TEMPBUFSIZE 0x003fffff`: These maximums correspond to the largest file size possible under the 4GB DWORD limit.

## B.5.2 SCCOPT\_TEMPDIR

From time to time, the technology needs to create one or more temporary files. This option sets the directory to be used for those files.

It is recommended that this option be set as part of a system to clean up temporary files left behind in the event of abnormal program termination. By using this option with code to delete files older than a predefined time limit, the OEM can help to ensure that the number of temporary files does not grow without limit.

---

**Note:** This option will be ignored if `SCCOPT_REDIRECTTEMPFILE` is set.

---

### Handle Types

`NULL`, `VTHDOC`

### Scope

Global

### Data Type

`SCCUTTEMPDIRSPEC` structure

### B.5.2.1 SCCUTTEMPDIRSPEC Structure

This structure is used in the SCCOPT\_TEMPDIR option.

SCCUTTEMPDIRSPEC is a C data structure defined in sccvw.h as follows:

```
typedef struct SCCUTTEMPDIRSPEC
{
    VTDWORD    dwSize;
    VTDWORD    dwSpecType;
    VTBYTE     szTempDirName[SCCUT_FILENAMESIZE];
} SCCUTTEMPDIRSPEC, * LPSCCUTTEMPDIRSPEC;
```

There is a limitation in the current release. dwSpecType describes the contents of szTempDirName. Together, dwSpecType and szTempDirName describe the location of the source file. The only dwSpecType values supported at this time are:

- IOTYPE\_ANSIPATH: Windows only. szTempDirName points to a NULL-terminated full path name using the ANSI character set and FAT 8.3 (Win16) or NTFS (Win32 and Win64) file name conventions.
- IOTYPE\_UNICODEPATH: Windows only. szTempDirName points to a NULL-terminated full path name using the Unicode character set and NTFS file name conventions. Note that the length of the path name is limited to SCCUT\_FILENAMESIZE bytes, or (SCCUT\_FILENAMESIZE / 2) double-byte Unicode characters.
- IOTYPE\_UNIXPATH: X Windows on UNIX platforms only. szTempDirName points to a NULL-terminated full path name using the system default character set and UNIX path conventions.

Specifically not supported at this time is IOTYPE\_REDIRECT.

#### Parameters

- dwSize: Set to sizeof(SCCUTTEMPDIRSPEC).
- dwSpecType: IOTYPE\_ANSIPATH, IOTYPE\_UNICODE or IOTYPE\_UNIXPATH
- szTempDirName: The path to the directory to use for the temporary files. Note that if all SCCUT\_FILENAMESIZE bytes in the buffer are filled, there will not be space left for file names.

### B.5.3 SCCOPT\_DOCUMENTMEMORYMODE

This option determines the maximum amount of memory that the chunker may use to store the document's data, from 4 MB to 1 GB. The more memory the chunker has available to it, the less often it needs to re-read data from the document.

#### Handle Types

NULL, VTHDOC

#### Scope

Global

#### Data Type

VTDWORD

**Parameters**

- SCCDOCUMENTMEMORYMODE\_SMALLEST 1 - 4MB
- SCCDOCUMENTMEMORYMODE\_SMALL 2 - 16MB
- SCCDOCUMENTMEMORYMODE\_MEDIUM 3 - 64MB
- SCCDOCUMENTMEMORYMODE\_LARGE 4 - 256MB
- SCCDOCUMENTMEMORYMODE\_LARGEST 5 - 1 GB

**Default**

SCCDOCUMENTMEMORYMODE\_SMALL 2 - 16MB

**B.5.4 SCCOPT\_REDIRECTTEMPFILE**

This option is set when the developer wants to use redirected IO to completely take over responsibility for the low level IO calls of the temp file.

**Handle Types**

NULL, VTHDOC

**Scope**

Global (not persistent)

**Data Type**

VTLPOID: pCallbackFunc

Function pointer of the redirect IO callback.

Redirect call back function:

```
typedef
{
    VTDWORD (* REDIRECTTEMPFILECALLBACKPROC)
    (HIOFILE *phFile,
    VTVOID *pSpec,
    VTDWORD dwFileFlags);
```

There is another option to handle the temp directory, SCCOPT\_TEMPDIR. Only one of these two can be set by the developer. The SCCOPT\_TEMPDIR option will be ignored if SCCOPT\_REDIRECTTEMPFILE is set. These files may be safely deleted when the Close function is called.





---

---

# Index

## Symbols

---

\$HOME, 3-6  
\$LD\_LIBRARY\_PATH, 3-6  
\$LIBPATH, 3-6  
\$ORIGIN, 3-5  
\$PATH, 3-6  
\$SHLIB\_PATH, 3-6

## A

---

Architectural Overview, 1-3  
Archive Record, 7-11

## C

---

CACloseContent, 6-1  
CAOpenContent, 6-1  
CAREadFirst, 6-2  
CAREadNext, 6-2  
casample, 10-2  
Character Mapping, B-1  
Compression, B-9  
Content Access Flags, B-10  
Content Access Functions, 6-1  
Content Access Options, B-1  
Content Breaks, 7-9  
Content Description, 7-1  
Copyright Information, 1-7  
Copyrights and Licensing, A-1

## D

---

DACloseDocument, 4-5  
DACloseTreeRecord, 4-16  
DADeInit, 4-2  
DAGetErrorString, 4-8  
DAGetFileId, 4-7  
DAGetFileIdEx, 4-7  
DAGetObjectInfo, 4-9  
DAGetOption, 4-6  
DAGetTreeCount, 4-10  
DAGetTreeRecord, 4-10  
DAInit, 4-1  
DAOpenDocument, 4-2  
DAOpenRandomTreeRecord, 4-12  
DAOpenTreeRecord, 4-11

DARetrieveDocHandle, 4-5  
DASaveInputObject, 4-13  
DASaveRandomTreeRecord, 4-14  
DASaveTreeRecord, 4-13  
DASetFileAccessCallback, 4-17  
DASetOption, 4-5  
DASetStatCallback, 4-16  
Data Access Common Functions, 4-1  
DAThreadInit, 4-1  
DATREENODELOCATOR, 4-12, 4-15  
Definition of Terms, 1-4  
Directory Structure, 1-5  
DisplayWndProc, 10-3  
Document Conventions, 0-ix  
Document Property IDs, 7-3  
DoSaveTextAs, 10-4  
DoTextBlockAccess, 10-4  
DoTextClose, 10-4  
DoTextOpen, 10-3

## E

---

environment variables, 3-5  
    \$HOME, 3-6  
    \$LD\_LIBRARY\_PATH, 3-6  
    \$LIBPATH, 3-6  
    \$PATH, 3-6  
    \$SHLIB\_PATH, 3-6

## F

---

File Property Content, 7-9  
File System, B-12

## G

---

Generated Information, 7-10

## H

---

How to Use Content Access, 1-5  
How to Use Text Access, 1-6

## I

---

Implementation Issues, 9-1

Input Handling, B-4  
Introduction, 1-1  
IOClose, 8-2  
IOGENSECONDARY and IOGENSECONDARYW  
Structures, 8-6  
IOGetInfo, 8-5  
IOGETINFO\_GENSECONDARY, 8-7  
IORead, 8-2  
IOSeek, 8-4  
IOSPECARCHIVEOBJECT Structure, 4-4  
IOSPECLINKEDOBJECT Structure, 4-4  
IOSPECSUBOBJECT Structure, 4-4  
IOTell, 8-4  
IOWrite, 8-3

## L

---

Licensing, A-1  
Linux  
    Compiling and Linking, 3-12  
    GLIBC and Compiler Versions, 3-9  
    Libraries on Linux Systems as Distributed  
        (IA32), 3-9  
    Libraries on Linux Systems as Distributed  
        (IA64), 3-11  
    Library Compatibility, 3-8  
    Motif Libraries, 3-8  
    Other Libraries, 3-9  
Linux 64-bit, 3-12  
Linux Compiling and Linking, 3-8  
Linux zSeries, 3-12

## M

---

Mail Field IDs, 7-6  
MainWndProc, 10-3

## N

---

NSF Support, 2-2, 3-1

## O

---

Oracle Solaris SPARC, 3-13  
Oracle Solaris x86, 3-13

## P

---

Preface, 0-ix

## R

---

Redirected IO, 8-1  
Running in 24x7 Environments, 9-1  
Runtime Search Path, 3-5

## S

---

Sample Applications, 10-1  
Samples  
    UNIX, 10-1

Windows, 10-1  
SCCBUFFEROPTIONS Structure, B-12  
SCCCA\_BEGINTAG, 7-1  
SCCCA\_BEGINTAG/SCCCA\_ENDTAG, 7-1  
SCCCA\_BREAK, 7-9  
SCCCA\_COMMENTREFERENCE, 7-8  
SCCCA\_FILEPROPERTY, 7-9  
SCCCA\_GENERATED, 7-10  
SCCCA\_OBJECT, 7-10  
SCCCA\_RECORD, 7-11  
SCCCA\_RECORD Content Description, 7-11  
SCCCA\_SHEET, 7-11  
SCCCA\_STYLECHANGE, 7-12  
SCCCA\_SUBDOCPROPERTY, 7-5  
SCCCA\_TEXT, 7-12  
SCCCA\_TREENODELOCATOR, 4-12, 4-15, 7-14  
SCCCAGETCONTENT Structure, 6-3  
SCCDAOBJECT Structure, 4-4  
SCCDATREENODE Structure, 4-11  
SCCOPT\_CA\_FLAGS, B-11  
SCCOPT\_DEFAULTINPUTCHARSET, B-1  
SCCOPT\_DOCUMENTMEMORYMODE, B-14  
SCCOPT\_ENABLEALLSUBOBJECTS, B-10  
SCCOPT\_EXTRACTXMPMETADATA, B-4  
SCCOPT\_FALLBACKFORMAT, B-4  
SCCOPT\_FIFLAGS, B-5  
SCCOPT\_FILTERJPG, B-9  
SCCOPT\_FILTERLZW, B-9  
SCCOPT\_FORMATFLAGS, B-11  
SCCOPT\_IGNORE\_PASSWORD, B-5  
SCCOPT\_IO\_BUFFERSIZE, B-12  
SCCOPT\_LOTUSNOTESDIRECTORY, B-6  
SCCOPT\_OUTPUTCHARACTERSET, B-2  
SCCOPT\_PARSEXMPMETADATA, B-6  
SCCOPT\_PDF\_FILTER\_REORDER\_BIDI, B-7  
SCCOPT\_PROCESS\_OLE\_EMBEDDINGS, B-7  
SCCOPT\_REDIRECTTEMPFILE, B-15  
SCCOPT\_TEMPDIR, B-13  
SCCOPT\_TIMEZONE, B-8  
SCCOPT\_UNMAPPABLECHAR, B-3  
SCCUTTEMPDIRSPEC Structure, B-14  
Sheet Names, 7-11  
Signal Handling, 3-5  
Status Callback Function, 4-16  
Style Information, 7-12  
SubObjects, 7-10

## T

---

TACloseText, 5-1  
tademo, 10-2  
Tag Types, 7-1  
Tagged Content, 7-1  
TAOpenText, 5-1  
TARadFirst, 5-2  
TARadNext, 5-3  
taredir, 10-4  
Text Access Functions, 5-1  
Text Content, 7-12  
textdemo, 10-4

Tree Node Locator, 4-12, 4-15, 7-14

## U

---

### UNIX

- API Libraries, 3-2
- Changing Resources, 3-6
- Character Sets, 3-4
- Double-Byte Character Set Mapping, 3-4
- Environment Variables, 3-5
- Filter Libraries, 3-3
- FreeBSD Compiling and Linking, 3-14
- HP-UX Compiling and Linking, 3-6
- HP-UX on Itanium, 3-7
- HP-UX on RISC, 3-7
- IBM AIX Compiling and Linking, 3-7
- Installation, 3-1
- Libraries and Structure, 3-2
- Options and Information Storage, 3-4
- Oracle Solaris Compiling and Linking, 3-12
- Premier Graphics Filters, 3-3
- Runtime Considerations, 3-5
- Support Libraries, 3-2
- UNIX Implementation Details, 3-1

## W

---

What's New in Release 8.3.7, 1-1

### Windows

- API DLLs, 2-2
- Changing Resources, 2-5
- Character Sets, 2-4
- Double-Byte Character Set Mapping, 2-5
- Filter DLLs, 2-3
- Installation, 2-1
- Libraries and Structure, 2-2
- Options and Information Storage, 2-4
- Premier Graphics Filters, 2-3
- Runtime Considerations, 2-5
- Structure Alignment, 2-4
- Support DLLs, 2-2
- Windows Implementation Details, 2-1

